

# RLM-W8

8,000 lumens, WUXGA, 3-chip DLP projector



Barco's RLM-W8 brings the saturated colors of 3-chip DLP™ projection to events and fixed installations, at the price of single-chip DLP™ technology.

## Featuring blending and built-in warping

With an enhanced contrast, quick and creative stacking options as well as built-in warping capabilities for curved surfaces, Barco's RLM-W8 is a versatile choice for mid- to large-sized venues. In addition, it features blending technology to create seamless composite images across a canvas of any size. The RLM-W8 continues the RLM line's tradition of silence as well as low energy consumption.

## Fast signal distribution

Our proprietary BarcoLink technology guarantees swift signal distribution between Barco's projectors and image processors. With BarcoLink, signals are distributed over a BNC coax cable, which is not only more durable but also enables you to lower your costs.

**BARCO**

Visibly yours

**Product specifications****RLM-W8**

<b>Projector type</b>	WUXGA 3-chip DLP digital projector
<b>Technology</b>	0.67" DMD™ x3
<b>Resolution</b>	1,920 x 1,200
<b>Brightness</b>	8,000 center lumens / 7,300 ANSI lumens*
<b>Contrast ratio</b>	2,200:1 (standard) / 3,000:1 (CE)
<b>Brightness uniformity</b>	95%
<b>Aspect ratio</b>	16:10
<b>ScenergiX</b>	Horizontal and vertical edge blending
<b>Lens type</b>	RLDW
<b>Lenses</b>	(fix)0.77:1 ; 1.16:1 ; (zoom) 1.45-1.74 ; 1.74-2.17 ; 2.17-2.9 ; 2.9-4.34 ; 4.34-6.76
<b>Optical lens shift</b>	Vertical: -100% to +100% / Horizontal: -35% to +35% on zoom lenses
<b>Color correction</b>	P7
<b>Lamps</b>	2x330W
<b>Lamp lifetime</b>	1,500 hours (typical) / 2,000 hours (maximum)
<b>Transport with lamp</b>	Yes
<b>Lamp house, quick replace</b>	Yes, auto lamp select
<b>Lamp warranty (field replace/ factory replace)</b>	120 days, 500 hours
<b>Sealed DLP™ core</b>	Standard
<b>Optical dowsers</b>	standard
<b>Picture-in-picture</b>	Up to two sources simultaneously
<b>Orientation</b>	table - ceiling
<b>WARP</b>	Preset and customized values (RS232)
<b>Integrated web server</b>	Yes
<b>3D</b>	Passive circular polarized (optional)
<b>Inputs</b>	2 x HDMI (HDCP 1,3); 5-BNC (RGBHV, RGBS/RGBsB;YUV); VGA (RGBHV, RGBS/RGBsB; YUV); cinch (RGBs, YUV); Composite video; S-Video; HSDI/ 3G HSDI /SDI/BarcoLink
<b>Input resolutions</b>	From NTSC up to UXGA (1600x1200), including WUXGA (1920x1200)
<b>Max. pixel clock</b>	165 MHz
<b>Software tools</b>	Projector Toolset, Android app
<b>Control</b>	Minijack + IR, RS232, 12v trigger
<b>Network connection</b>	10/100 base-T, RJ-45 connection
<b>Power requirements</b>	90-240V / 50-60Hz
<b>Max. power consumption</b>	850W / STBY
<b>Noise level (typical at 25°C/77°F)</b>	39dB(A)
<b>Operational ambient temperature</b>	0-40°C / 32°-104°F
<b>Operational humidity</b>	0-80% (non condens)
<b>Dissipation BTU</b>	max 2900 BTU/h
<b>Dimensions (WxLxH)</b>	500 x 669.74 x 247mm / 19.69 x 26.36 x 9.72 inches
<b>Weight</b>	26kg (57.3lbs)
<b>Shipping Dimensions</b>	(LxWxH) 820 x 660 x 380mm / 32.28 x 25.98 x 14.96 inches
<b>Shipping Weight from Factory</b>	30kg (66.1lbs)
<b>Standard accessories</b>	Power cord, wireless remote control, HDMI to DVI converter
<b>Certifications</b>	Compliant with FCC rules and regulations, part 15 Class A and CE EN55022 Class A, CE, TUV, RoHS, WEEE
<b>Warranty</b>	3 years standard, 4th or 5th year optional
<b>*</b>	+/- 10%

Last updated: 20 Apr 2016  
Technical specifications are subject to change without prior notice.  
Please check [www.barco.com](http://www.barco.com) for the latest information.

**BARCO**

Visibly yours