

CP755ew

Huge Light For Small Places

The CP755ew is our top performing projector for short-throw presentations. Capable of sitting as close as 1.8 feet from the screen or image surface, it lends versatility and functionality to any situation where space is limited.



CP755ew

Specifications



BRIGHTNESS

3000 (Standard)

2400 (Economy)

RESOLUTION

1024 x768 XGA (Native)

1280x1024 SXGA (Supported)

DISPLAY TYPE

0.63" HTPS TFT LCD x3

CONTRAST RATIO

500 :1

ASPECT RATIO

4:3 Native

16:9 Compatible

THROW RATIO

1.0 ~ 1.2 (x screen width)

PROJECTION LENS

Manual Zoom & Focus

ZOOM RATIO

1.0~1.2:1

DIAGONAL IMAGE SIZE

40" - 300"

THROW DISTANCE

1.8' - 24'

KEystone

+/- 30° Vertical

LAMP

200 watt NSH

LAMP LIFE

2000 (Standard)

3000 (Economy)

INPUTS

VGA (Computer 2/YPbPr)

VGA Computer 1

S-Video

Composite Video

Audio (3.5 mm)

OUTPUTS

Audio (3.5 mm)

VGA

PROJECTOR CONTROLS

USB

RS232 (DIN)

COMPATIBILITY

VGA,SVGA,XGA,SXGA, Mac

EDTV / SDTV / HDTV

480i/p,720p,1080i

FCC CERTIFICATION

FCC-B, UL, TUV-CB, c-UL, CB, CE, CCC

VIDEO COMPATIBILITY

NTSC / NTSC 4.43 / PAL B/G/H/I/M/N 60 /

SECAM

AUDIO

1 x 2w Mono Speaker

DECIBEL RATING

33dB (Standard) / 30dB (Economy)

H-REFRESH RATE

15-90 kHz

V-REFRESH RATE

50-85 kHz

POWER SUPPLY

AC 110 ~ 240 Volts

(Auto Ranging)

POWER CONSUMPTION

250 Watts AVG

DIMENSIONS (WxDxH)

12.2" x 10.6" x 4.6"

WEIGHT

7.3 Lbs

WARRANTY

3 year parts & labor / 90 day lamp

Special features of the CP755ew include:

3-D comb filtering—

Eliminates artifacts resulting in better video quality.

Auto brightness—

Detects ambient light and adjusts brightness, extending lamp life.

Auto keystone correction—

Projector will automatically correct a trapezoidal image.

Unplug & Go—

No need to wait for the projector to cool down. Just unplug and go!

