Seattle X35N

The Brighter Side of Projection

BOXLIGHT

Delivering 3500 lumens of bright light and sharp XGA resolution, it is no wonder the Seattle X35N is one of our best selling projectors. Its consistent performance and easy-to-use functionality make it ideal for a wide variety of applications and audiences.

- Robust input panel
- LAN control
- Password security
- Closed caption
- RS232
- Optional harsh enviro filter
- Side changing lamp & filter
- Quick startup and shutdown
- · 8 watt speaker





Seattle X35N

Specifications

L C BOXUGHT

BRIGHTNESS

3500 Lumens (Standard) 2300 Lumens (Economy)

RESOLUTION

1024x768 XGA (Native) 1600x1200 UXGA (Compatible)

DISPLAY TYPE

0.63″ LCD w/ MLA x 3

CONTRAST RATIO

500 :1

ASPECT RATIO

4:3 Native 16:9 Compatible

THROW RATIO

1.45 ~ 1.73 (x screen width)

PROJECTION LENS

Manual Zoom & Focus

ZOOM RATIO

1.2:1 DIAGONAL IMAGE SIZE

40″ - 300″ 101.6cm - 762cm

THROW DISTANCE

3.33' - 25' 1.01m - 7.62m

KEYSTONE

+/- 30º Vertical

LAMP

230 watt UHP

LAMP LIFE

2000 (Standard) 3000 (Economy)

INPUTS

VGA DVI-I S-Video Composite Component Audio x 2 (3.5mm)

OUTPUTS

VGA Audio (3.5mm) PROJECTOR CONTROLS

USB RS232 (9-pin) RJ45 LAN Connection

COMPATIBILITY

VGA, SVGA, XGA, SXGA, UXGA, Mac EDTV / SDTV / HDTV 480i/p, 576i/p, 720p, 1080i FCC CERTIFICATION FCC-B, UL, cUL, TUV, CD, CE, CCC VIDEO COMPATIBILITY NTSC, NTSC 4.43, PAL M/N 60,

SECAM

AUDIO

1 x 8w Mono Speaker **DECIBEL RATING**

33 dB (Standard) / 30 dB (Economy)

H-REFRESH RATE

31-92 kHz

V-REFRESH RATE

48-120 Hz

POWER SUPPLY

AC 100 ~ 240 Volts 50-60Hz (Auto ranging)

POWER CONSUMPTION

RS232 Audio In 1 RGB In DVI-I In

•••• أ • الله •

•())

Ô

ø

Audio In 2 Audio Out RGB Out

310 Watts (Standard) <5w standby

DIMENSIONS (WxDxH)

12.8" x 10.24" x 3.8" 32.5cm x 26cm x 9.7cm

WEIGHT

7.3 lbs 3.3 kg

WARRANTY

3 year parts & labor / 90 day lamp

Special features of the Seattle X35N include:

LAN Connectivity – For network installation. Manage your projectors through a web-based platform.

Quick Start Up and Shut Down— Set up and present quickly, and only a 10 second cool down cycle when you finish.

Side Changing Lamp and Filter-Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.

Audio In 3

LAN

(R/L)

00

0


Compo

Y/Pb/Pr

S-Video

AC N

Video



Diagonal Image Size (Inches)



www.boxlight.com 360.464.2119

Speaker

Rear IR receiver

Kensington Micro Saver Slot