

TraveLight2

Get up and go.

This projector is so light, compact and portable, it should become standard equipment for all on-the-go presenters. Traveling business executives, trainers, educators and government representatives all speak to its easy-to-manuever performance.



TravelLight2

Specifications



BRIGHTNESS

2100 Lumens (Standard)

1600 Lumens (Eco)

RESOLUTION

1024 x 768 XGA

1600X1200 UXGA (Supported)

DISPLAY TYPE

Texas Instruments

0.7" x 1, 12° DDR

CONTRAST RATIO

2000 :1

ASPECT RATIO

4:3 Native

16:9 Compatible

THROW RATIO

1.8 ~ 2.1 (x screen width)

PROJECTION LENS

Manual Zoom / Focus

ZOOM RATIO

1.16:1

DIAGONAL IMAGE SIZE

35" - 200"

THROW DISTANCE

4.9' - 23' Feet

KEystone

+/- 15° Vertical

LAMP

156 watt OSRAM VIP

LAMP LIFE

4000 Standard

5000 Eco

INPUTS

Audio (3.5mm)

DVH (component)

Composite (3.5 mm)

S-Video (3.5 mm)

OUTPUTS

N/A

PROJECTOR CONTROLS

USB

COMPATIBILITY

VGA, SVGA, XGA, SXGA,

UXGA, Mac

EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

FCC CERTIFICATION

FCC-B, UL, TUV-CB, UL, CB, CE, CCC

VIDEO COMPATIBILITY

NTSC / NTSC 4.43 / PAL B/G/H/I/M/N 60 /

SECAM

AUDIO

1 x 0.5w Mono Speaker

DECIBEL RATING

37dB (standard) / 32dB (eco)

H-REFRESH RATE

15-90 kHz

V-REFRESH RATE

50-85 kHz

POWER SUPPLY

AC 110 ~ 240 Volts

(auto ranging)

POWER CONSUMPTION

190W (standard)

165W (eco)

DIMENSIONS (WxDxH)

7.7" x 6.4" x 2.2" Inches

WEIGHT

2.5 Lbs

WARRANTY

3 year parts & labor / 90 day lamp

Special features of the TravelLight2 include:

Extreme portability— Just 2.5 lbs!.

Fan speed control—

Optional fan speeds for use in high altitude locations.

Menu reset option—

Reset various settings without defaulting all the projectors settings.

Auto keystone correction—

Projector will automatically correct a trapezoidal image!

