

8792H

ImagePro 8792H Portable LCD Projector



The ImagePro 8792H is a light (5 lbs), easy-to-use portable LCD projector ideal for classroom or conference room.

8792H FEATURES

- 3200 Lumens Brightness
- XGA Resolution
- Lamp access on top
- High performance 5,000 hour, Hybrid filter with easy side access
- Short throw distance, 1.3 to 1.5
- New 3000/4000 hour lamp
- Built-in Anti-theft security
- Audio "passthrough" permits use of sound system to play CDs on the PC when projector is off
- HDMI input (HDCP compliant)



NEW SIDE-LOADING FILTER PROVIDES EASY FILTER MAINTENANCE

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

 **Convey**
SOLUTIONS

Convey by Dukane delivers control of classroom audio visual assets in sync with our Convey AClick Student Response System. Experience tomorrow's classroom today with Convey. Visit www.conveyclassrooms.com.
Call Dukane: 866.280.4298

Toll-free: 888-245-1966 • Web: www.dukane.com/av
Fax: 630-584-5156 • E-mail: avsales@dukane.com

ImagePro 8792H Portable LCD projector

Back Panel

Connections



Key features:

- XGA (1024 x 768) resolution
- 3200 ANSI lumens of brightness
- Whiteboard & Blackboard Modes
- Easy maintenance in ceiling mount with lamp access on top and 5,000 hour Hybrid filter with side access
- Monitor loopthrough
- Instant On and Off
- Short throw distance
- Audio passthrough for sound when projector is off
- 3000/4000 hour lamp life
- Lock slot, security bar and transition detector
- Five Year Warranty and One Year Peace of Mind Service

8792H Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	2.5	3.0
60	48	5.1	6.1
80	64	6.8	8.1
100	80	8.5	10.2
120	96	10.2	12.3
150	120	12.8	15.3
200	160	17.0	20.4
300	240	25.4	30.5

Throw Ratio (distance to width) 1.3 1.5

THE ALL NEW
DUKANE
Education. Presentation. Inspiration.

Audio Visual Products
2900 Dukane Drive
St. Charles, Illinois 60174
Toll-free: 888-245-1966
Fax: 630-584-5156
E-mail: avsales@dukane.com
Web: www.dukane.com/av



ImagePro is a registered trademark of Dukane Corporation

Specifications

Image Element	0.63" polysilicon active-matrix TFT x3
Brightness	3200 ANSI lumens (2500 lumens in Whisper Mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	500:1
Scanning Frequency	fh 15 -106 kHz, fv 50-120 Hz
Lens	Manual zoom 1.2X
Lens Throw Ratio	1.3 -1.5:1 throw distance to image width
Keystone Correction	Digital, vertical +/-30 deg
Aspect Ratio	4:3, 16:9 selectable
Computer	SVGA, VGA, XGA, SXGA, UXGA
Compatibility	MAC16"
Video Compatibility	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, Component Video, HDTV (1080i/p, 720p, 576i, 480i/p)
Image Control	Freeze function, electronic magnification and pan
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	200W UHP
Lamp Life	3000 hours (typical) 4000 hours (whisper mode)
Audio Output	1 watt
Throw Distance	30" to 387"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, Share with RGB (1) Composite video, RCA x 1 (1) S-Video, mini DIN 4-pin (1) HDMI
Inputs, Computer	(1) RGB, 15 pin D-sub, component
Inputs, Audio	(2) Stereo mini jack
Outputs, Audio	(1) Stereo mini jack, adjustable level
Outputs, Monitor	RGB, 15 pin D-sub
Control	9 pin, D-sub, RS-232
Security	Kensington lock slot & Security Bar
Fan Level	35dB, ultra quiet; 29dB Whisper Mode
Closed Caption	For NTSC only
Operating Temperature	41-95 deg F
Power	AC 100-120V, AC 220-240V 50/60 Hz, 290 watt
Size (WxHxD)	12" x 3.0" x 8.7"
Weight	5 lbs.
Shipping Weight	15 lbs.
Carton Size	15" x 8" x 19" (est.)
Accessories Included	Remote control, batteries, power cord, RGB cable, operation manual
Safety Agency	UL/C-UL, FCC Class B, CE, ROHS
Optional Accessories	Lamp 456-8789 Ceiling Mount, Universal; RPM-U Filter: UX36761

Five (5) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

5YR