



ELECTRONIC - VGA SWITCHER/DISTRIBUTOR



DESCRIPTION

The VP-222 is a high performance switcher for computer graphics video signals with resolutions ranging from VGA through UXGA and higher. It switches one of two inputs to two identical outputs.

- High Bandwidth - 365MHz (-3dB).
- HDTV Compatible.
- Compact Size - Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.

SPECIFICATIONS

INPUTS:	2 analog red, green, blue signals - 0.7 Vpp/75Ω, H & V sync, TTL level, on HD15F connectors.
OUTPUTS:	2 analog red, green, blue signals - 0.7 Vpp/75Ω, H & V syncs, TTL level, on HD15F connectors.
VIDEO BANDWIDTH (-3DB):	365MHz.
NON-LINEARITY:	0.1%.
DIFF. GAIN:	0.06%.
DIFF. PHASE:	0.04 Deg.
K-FACTOR:	0.05%.
VIDEO S/N RATIO:	76dB.
CROSSTALK:	-52dB @ 5MHz.
POWER SOURCE:	12 VDC, 120mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98", W, D, H.).
WEIGHT:	0.25kg. (0.55 lbs.) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	Model VA-50P power supply with six 12VDC outlets.RK-T1, RK-T3, 19" rack adapters.

