

TW766W – Widescreen Installation Projector

A Complete Package of Widescreen Versatility and Performance

Perfect for challenging installations, the Optoma TW766W mixes performance and integration features to create an outstanding choice for conference rooms, auditoriums and classrooms. With 4000 ANSI lumens and Optoma's exclusive PureShift technology, the TW766W provides bright, sharp images in any installation. Cable-free projection with standard wireless connectivity saves time and greatly simplifies usage and setup.



Features

- Easy-to-view images even from the back of the room – high brightness at 4000 ANSI lumens and contrast at 2500:1
- Native WXGA resolution is an ideal match for widescreen PCs and laptops
- Flexible projector placement – PureShift allows for vertical and horizontal lens shift and a 1.6x zoom provides for a wide range of installations
- Internal wireless connectivity provides a link for both data and video from up to four computers simultaneously
- Remote monitoring and control capabilities over a LAN network via integrated RJ45 connection
- Complete security features protect projector settings and lock out unauthorized users through both wired and wireless network connections



Specifications

Display Technology

Single 0.65" DarkChip2™ DLP® Technology by Texas Instruments

Resolution

Native WXGA (1024 x 768)

Maximum Resolution

WUXGA (1920 x 1200)

Brightness (Typical)

4000 ANSI Lumens

Contrast Ratio

2500:1 (Full On/Full Off)

Lamp Life and Type

3000/2000 Hours (STD/Bright)
280W UHP

Throw Ratio

1.57-2.39:1 (Distance/Width)

Projection Distance

3.9' to 32.8' (1.2 to 10m)

Image Size (Diagonal)

23.2" to 295.7" (0.59 to 7.51m)

Aspect Ratio

16:10 Native, 16:9 and 4:3
Compatible

Audio

Two 2-Watt Speakers

Remote Control

Fully Featured Remote Control
w/Mouse and Laser Pointer

Displayable Colors

134.2 Million

Keystone Correction

±30° Vertical

Uniformity

85%

Computer Compatibility

WUXGA, UXGA, SXGA+, XGA, SVGA,
VGA Resized, VESA, PC and
Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, SDTV (480i),
EDTV (480p), HDTV (720p, 1080i/p)

Monitor Loop Through

D-Sub 15-Pin VGA Output (Functional
in Both Normal and Standby Modes)

Lens Shift

Vertical 105-130% Offset,
Horizontal ±30% Image Width at
V=105%

Projection Lens

F= 2.41-3.2, f = 22.18-33.27 mm,
1.5x Manual Zoom and Focus

User Controls

Complete On-Screen Menu
Adjustments in 23 Languages

I/O Connectors

HDMI (Audio Supported), DVI-D
w/HDCP, Two VGA-In, VGA-Out,
S-Video, Composite Video, Two
Mini-Jack Audio-In, RCA Audio-In,
Mini-Jack Audio-Out, USB, RS-232,
RJ45, +12V Trigger

Security

Kensington® Lock Port, Password
Protection, Wireless WEP Key

Projection Method

Front, Rear, Ceiling Mount, Table Top

Weight

12 lbs (5.4kg)

Dimensions (W x H x D)

14.3" x 5" x 11.1" (364 x 127 x 283mm)

Noise Level (STD/Bright)

30dB/32dB

Horizontal Scan Rate

15 to 91 kHz

Vertical Refresh Rate

50 to 85 Hz

Operating Temperature

41 to 95°F (5 to 35°C), 80% Max
Humidity, Adjustable Fan Speed for
High Altitude Application

Power Supply

AC Input 100-240V, Auto-Switching

Standard Accessories

AC Power Cord, VGA to VGA
Cable, USB Cable, RS-232 Cable,
Remote Control, Batteries for
Remote, Lens Cap, CD-ROM
User's Manual, Quick Start Card,
Warranty Card

Optional Accessories

Ceiling Mount, S-Video Cable,
Audio-Out Adapter, HDMI Cable,
Composite Video Cable, DVI Cable,
Panoview™ Series Screens

Warranty

3 Years Optoma Express
Replacement Service, 1 Year on
Lamp

UPC

796435 41 123 7

Accessory Part Numbers

Lamp: BL-FU280B
Remote: BR-5029L
Mount: BM-5001U