

PDG-DSU21N

SVGA Ultraportable Multimedia Projector



ULTRA-COMPACT, FULLY PORTABLE SVGA DESIGN

Not much larger than a laptop PC, the PDG-DSU21N weighs less than 6.0 pounds and delivers true SVGA picture quality in a versatile, go-anywhere system.

HIGH BRIGHTNESS AND CONTRAST

A brightness level of 2300ANSI Lumens and a contrast ratio of 2000:1 make this projector a winner in its category. It's all the quality DLP® technology has become known for.

BETTER CONTROL

The PDG-DSU21N comes with an RS232C control port x1 for advanced projection control.

F2.51 - 2.69 ZOOM LENS

Comes with its own 1:1.1 zoom lens, which can throw a crisp, bright 100" diagonal image. That's just one size. This lens is adjustable up to a 300-inch diagonal screen size.

AUTO INPUT SEARCH

This special feature searches, finds and displays incoming source material automatically.

SPECIAL FEATURES

Component input, quiet fan operation and versatile go anywhere capability make this a truly portable projector. Also may be ceiling or inverse mounted for enhanced versatility.



DLP® and the DLP logo are registered trademarks of Texas Instruments. BrilliantColor™ and DynamicBlack™ are trademarks of Texas Instruments.

PRESENTATION TECHNOLOGIES



21605 Plummer Street
Chatsworth, CA 91311
Ph: 888-337-1215 (toll-free)
Fax 818.717.2719
www.sanyoprojectors.com

Specifications

Resolution	SVGA (800 x 600)
Brightness	2300 ANSI Lumens
Uniformity	80% (corner to center)
LCD Panel System	0.55" DMD x 1
Number of Pixels	480,000(800 x 600)
Contrast Ratio	2000:1
Image Size (diagonal)	30" – 300"
Aspect Ratio	4:3
Throw Distance	3.9' – 39.4'
Zoom/Focus	Manual
Zoom Ratio	1:1.1
Up/Down Ratio	13.3:-1
Digital Keystone Correction	Vertical: +/- 15° MAX
Projection Lens	F2.51-2.69 / f0.86"-0.95"
Lens Throw Ratio	1.95-2.15:1
Projection Lamp	180W UHP
Scanning Frequency	H 31-79kHz; V 50-85Hz
Dot Clock	25-135MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	SXGA, XGA, SVGA, VGA
Sound Output	One-piece, 2-watt Mono
Voltage	100-240V AC (auto voltage) ; 50/60 Hz
BTU Rating	786
dB Rating	35dBA / 32dBA (normal/eco)
Power Consumption	230W / 200W (normal/eco)
Dimensions (WxHxD)	10.7" x 3.2" x 8.8" (not including protrusion & lens part)
Net Weight	6.0lbs
User Maintenance	Clean air filters, replace lamp assembly
PC Input Terminals	D-Sub15 x 1
Video Input Terminals	Composite video (RCA x 1) • S-Video (mini-Din 4-pin) • Audio(stereo mini-jack : common) • Computer/Component In (D-sub 15x1)
Control Terminals	• USB (type B) • RS232C control port x 1
Included Accessories	Wireless remote • CR2025 batteries • Owner's manual • VGA cable • Lens cap with strap • AC power supply cord • Quick start guide
Optional Accessories	• 610 337 1764 – Replacement lamp • 645 096 2523 – Replacement remote • POA-CA-COMPVGA – Component – VGA conversion cable • POA-MCSRL02 – Serial cable • POA-CAC-VCL2 – Soft carrying bag
Service Port	n/a
Warranty	Three years parts and labor; 90 days original lamp; Quick repair program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Remote Control
645 096 2523



Rear Back Panel