

# PLC-WXU300

**Light weight. WXGA Portable Multimedia Projector**



### TRUE WXGA (1280 x 800) RESOLUTION

Compatible with wide screen laptops for an accurate wide screen WXGA (16:10) presentation. The PLC-WXU300 has an HDMI input terminal which is the most popular port for wide aspect ratio projector.

### PICTURE IN PICTURE ( P IN P ) AND PICTURE BY PICTURE ( P BY P ) FUNCTION

Capable of projecting two images simultaneously by using either "P in P" and "P by P" functions. These functions are useful in video conferencing and educational systems.

### COMPLETE EASY AUTO SET UP FUNCTION

PLC-WXU300 provides "Auto Set Up Function" that corrects keystone shaped distortion by searching for an input signal and detecting projector incline, therefore reducing set up time. PLC-WXU300 automatically compensates for keystone picture distortion. Auto Keystone Correction, Auto Input Search and Auto PC Adjustment make it a really smart projector.

### SHORT THROW LENS WITH 1.6 ZOOM AND 7W SPEAKER

PLC-WXU300 is equipped with a zoom lens that allows screen size adjustment. The short-focus type lens allows large screen image projections with a short throw distance. The PLC-WXU300 enables 100-inch screen projection at the shortest distance, 100 inches. The PLC-WXU300 features a high-output 7 Watt speaker. Sufficient audio is delivered through its built-in speaker, so the projector can be used in conference rooms, classrooms, and other similar spaces.

### Wired LAN (RJ-45) for projector control

This model is equipped with Wired LAN (RJ-45) that allows you to manage and control the projector via Network. It is possible to check the operating time of lamp and manage the warning notification by email. Power ON/OFF and switching of the input signal can be controlled. You can save a lot of time in manage and control.

### BLACK BOARD / COLOR BOARD MODE

The PLC-WXU300 is compatible with black and four variously colored (red, blue, green, and yellow) projection surfaces via 'Black (Color) Board Mode' without a screen.

### POWER OFF AND GO

An easy-off function enables the projector to be unplugged immediately without waiting for the lamp to cool down.

### CLOSED CAPTION

PLC-WXU300 Closed Caption compatible.



PRESENTATION TECHNOLOGIES  
 21605 Plummer Street  
 Chatsworth, CA 91311  
 Ph: 888-337-1215 (toll-free)  
 Fax: 818-717-2719  
 www.sanyoprojectors.com

## Specifications

Resolution	WXGA (1,280 x 800)
Brightness (typical)	2,500 ANSI
Uniformity	85%
Panel System	0.59" TFT Poly x 3
Number of Pixels	3,072,000 (1,024,000 x 3)
Contrast Ratio (Full on / off)	500:1
Image Size	30" - 300"
Aspect Ratio	16:10
Projection Lamp (s)	225W UHP
Scanning Frequency	H:15-100KHZ V:50-100Hz
Dot Clock	140MHz
Fan Noise	29dBA (eco)
Voltage	100-240V
BTU Rating	1061 / 768 (Normal / Eco)
Power Consumption	311W / 225W (Normal / Eco)
Input signal compatibility	WUXGA / WSXGA+ / WXGA+ / WXGA UXGA / SXGA+ / SXGA / XGA / SVGA / VGA, Analog : 480i / 480p / 575i / 575p / 720p (50/60) / 1080i (50/60) HDMI : 480p / 575p / 720p (50/60) / 1080i (50/60) / 1080p (50/60)
Color System	NTSC / PAL / SECAM / NTSC4.43 / PAL-M / PAL-N
Projection Lens (inch)	F1.65-2.33 f=0.61" - 0.97"
Throw Ratio	1.18 - 1.91
Throw Distance (feet)	2.4' - 25.2'
Zoom / Focus	Manual
Zoom Ratio	1:1.6
Up / Down Ratio	49:1
Digital Keystone Correction	V +/- 30° (Auto Keystone)
Projection System	Dichroic mirror and X prism system with PBS
Digital Zoom	16x - 1/4x
Speaker Output	7W
Weight (lbs.)	6.2 lbs
Dimensions (inch) W,H,D	12.8" x 3.3" x 9.1"
Lamp Life * (hours Normal / Eco)	Up to 4000h / 5000h (Normal / Eco)
Replacement Lamp	610 343 2069
Replacement Remote	645 099 3190
Input	Dsub-15 x 2 (IN-1: Component/Scart RGB common use) HDMI x 1 (Digital) Mini jack x 2 (Audio input, stereo) Mini DIN 4-pin x 1 (S-Video) RCA x 1 (Composite Video) RCA x 2 (Audio input, R/ L-mono)
Output	Dsub-15 x 1 (Monitor out : common use Input-2) Mini jack x 1 (Audio out, stereo variable)
Control	Dsub-9 x 1 (Control port)
Others	RJ-45 x 1 (Wired LAN)
Included Accessories	Quick reference guide, User's manual (CD ROM), CD-ROM read me note, UL cable card, PIN code label, Computer cable, Power cord, Remote control, AAA Battery x 2, PJ Network Manager software (CD ROM), Strap for Lens cap, Soft Carrying Bag
Optional Accessories	POA-CACOMPVGA-Component Video Cable
User Maintenance	Clean air filters, replace lamp assembly
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

\* Lamp life may vary due to room conditions, usage, and maintenance. The replacement time is a general estimate. The brightness of a lamp usually decreases over time and use.

### Terminals

