

PLC-WXU30

WXGA Ultraportable Multimedia Projector



FITS A VARIETY OF APPLICATION SITUATIONS

Offering a wide XGA full 1280 x 800 (16:10) resolution, the PLC-WXU30 makes it possible to project high-quality HD images from virtually any location. At 3700 lumens, this extremely bright, yet compact, projector is equally comfortable entertaining the whole family with exquisite HD images from cable/satellite or DVD sources as it is delivering a PC-based business presentation to a select audience in the work place. It also is ideal for projecting larger-than-life video from today's best game consoles.

FITS ANY SET-UP SITUATION

A flexible zoom lens allows for projecting in both short and long distances, from 3-feet to 39.7-feet, to be exact. Keystone correction adjusts for 40 degrees up or down for fast and easy set up.

NETWORKING CAPABILITY

The PLC-WXU30 is equipped with SANYO's exclusive PJ Network Interface for wired and wireless networking, a common feature among SANYO's extensive line of commercial projectors. Networking allows the monitoring of projector functions and operation from a long distance via a web browser. Emails can be sent automatically to report operating status. The wireless interface is compatible with IEEE802.11b/g standards, offering transfer speeds up to 54Mbps and providing WEP 64/128-bit security.

POWER OFF AND GO AND ANTI-THEFT ALARM

The units are designed with the Easy-Off function. It's possible to remove the power cord without waiting for the machine to cool down -- convenient for quickly clearing away a temporary set-up. As this projector is small and light, a pin code lock is provided to prevent theft. When activated, a loud audio alarm goes off to scare away would-be thieves.

VERSATILE INPUTS

The PLC-WXU30 offers excellent flexibility via DVI-I and D-Sub 15 inputs. It even has component video inputs. Additionally, there is a D-Sub -15 terminal for a monitor output, achieving greater programming flexibility.

PRESENTATION TECHNOLOGIES

21605 Plummer Street
 Chatsworth, CA 91311
 Ph: 888-337-1215 (toll-free)
 Fax 818.717.2719
 www.sanyolcd.com



Specifications

Resolution	WXGA (1280 x 800)
Brightness (typical)	3700 ANSI Lumens
Uniformity	85 %
LCD Panel System	0.7" TFT Poly x3
Number of Pixels	3,072,000 (1,024,000 x 3)
Contrast Ratio	500:1 (Lamp Mode "Auto", Image Mode "Dynamic")
Projection Image (diagonal)	40"-300"
Aspect Ratio	16:10
Throw Distance	3.2'-39.7'
Zoom/Focus	Manual (1:1.6 zoom)
Up/Down Ratio	49:1
Digital Keystone Correction	Vert. +/- 40°
Projection System	Dichroic mirror & 4P prism system w/ PBS
Projection Lens	F1.7-2.5 / f0.76"-1.19"
Lens Throw Ratio	1.16 - 1.86 :1
Projection Lamp	275W
Scanning Frequency	H 15-100kHz; V 50-100Hz
Dot Clock	140 MHz
Color System	NTSC/PAL/SECAM/NTSC4.43/PAL-M&N
Computer Compatibility	UXGA, WXGA, SXGA, XGA, SVGA, VGA, MAC analog
Sound Output	One-piece, 1-watt Mono
Voltage	100-120/200-240V AC; 50/60/Hz (auto sense/select)
BTU Rating	1242
dB Rating	30dBA(Eco mode)
Power Consumption	364W
Dimensions (WxHxD)	13.15" x3.07"x10.12" (not including Adjustable Feet)
Net Weight	7.9 lbs.
User Maintenance	Clean air filters, replace lamp assembly
PC Input Terminals	DVI-I x 1 (w/HDCP) ● D-Sub15 x 1 ● Audio x 1 (stereo mini-jack : common)
Video Input Terminals	Composite Video (RCA x 1) ● S-Video (mini-DIN 4-pin) ● R & L/mono audio (RCA x 2) ● Component Video (D-Sub15 input w/optional cable) ● Audio for Component Video (stereo mini-jack)
Output Terminals	D-Sub15 x 1 (Monitor Out) ● Variable Audio from PC Audio Input or Video Audio Input (Stereo Mini-Jack)
Service Port Terminal	Mini DIN 8-pin
Mouse Control Port	USB type B x 1
Other Terminals	USB for mouse control ● RJ45 for Wired LAN ● SD Card
Included Accessories	Wireless/wired remote control with Mouse Pad and Laser Pointer ● 2 AAA batteries ● Owner's manual (Quick manual & CD-ROM) ● VGA cable ● PIN code label ● AC power supply cord ● CD-ROM(Application soft) ● Alarm Protected Seal ● Soft Carry Bag ● Strap & Screw for Lends Cap
Optional Accessories	● POA-CACOMPVGA – Component Video cable ● 610 333 9740 – Replacement Lamp
Warranty	Three years parts and labor; 90 days Initial lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.



Rear Panel Terminals