






VP-725xl

21-Input ProScale™ Presentation Digital Scaler/Switcher



The **VP-725xl** is a presentation scaler/switcher with multiple signal format sections. The unit has five independent 4x1 video sections: composite, s-Video (Y/C), component (YUV), computer graphics, and HDMI, plus a single USB input. It also scales any video input up or down to a selectable graphics or HDTV output resolution and provides glitch-free switching between sources through FTB™ (fade-thru-black) switching technology.





VP-725xl

FEATURES

- **HQV® Video Processing** - HQV (Hollywood Quality Video) processing represents the state-of-the-art in video processing technology, with the highest quality de-interlacing, noise reduction, and scaling performance for both standard-definition and high-definition signals.
- **De-interlacing and Scaling** - High-quality 3:2 and 2:2 pull down, de-interlacing and full up and down scaling of computer graphics video input signals.
- **HDTV Compatible.**
- **HDCP Compliant** - The HDCP (High Definition Content Protection) license agreement allows only copy-protected data on the HDMI input to pass to the HDMI output.
- **Fade-Thru-Black (FTB™) Switching (Scale Output)** - The video fades to black and then the new input fades from black for smooth, glitch-free switching. The output signal provides constant sync so the display never glitches.
- **K-IIT XL™ Picture-in-Picture Image Insertion Technology** - Ultra stable picture-in-picture, picture-and-picture, and split screen capability. Any video source can be inserted into or positioned next to a computer graphics video source or vice versa with window positioning and sizing controls.
- **Projector Anywhere™ Technology** - Horizontal & vertical geometry controls compensate for off-axis projector placement.
- **Multi-Format** - Auto, NTSC (3.58/4.43), PAL (M/N/60) & SECAM.
- **6 Switchers in 1** - Five dedicated signal formats: 4x1 composite, 4x1 s-Video (Y/C), 4x1 component (RGB/YUV), 4x1 computer graphics (15-pin HD), 4x1 HDMI and one 21x1:3 scaled output.
- **USB Port** - For importing JPEG files.
- **Scaled Computer & HDTV Outputs** - A single output signal in 3 formats (15-pin HD, 5 BNCs, and HDMI) simultaneously.

TECHNICAL SPECIFICATIONS

INPUTS:	4 x CV 1Vpp/75Ω on BNC connectors; 4 x Y/C 1Vpp, (Y): 0.3Vpp (C)/75Ω on 4-pin connectors; 4 x component (Y/G, Pb/B, Pr/R or RGsB) on BNC connectors; 4 x VGA (VGA through UXGA, RGBS or RGsB2) on 15-pin HD connectors; 4 x HDMI on HDMI connectors.
GROUP OUTPUTS:	1 x CV 1Vpp/75Ω on a BNC connector; 1 x Y/C 1Vpp (Y): 0.3Vpp (C)/75Ω on a 4-pin connector; 1 x component (Y/G, Pb/B, Pr/R) on BNC connectors; 1 x VGA (VGA through UXGA) on a 15-pin HD connector; 1 x HDMI on an HDMI connector.
SCALED OUTPUTS:	1 x UXGA on a 15-pin HD connector; 1 x RGBHV/YPbPr on BNC connectors; 1 x HDMI on an HDMI connector.
OUTPUT RESOLUTIONS:	Native HDMI, 640x480@60Hz, 640x480@75Hz, 800x600@50Hz, 800x600@60Hz, 800x600@75Hz, 1024x768@50Hz, 1024x768@60Hz, 1024x768@75Hz, 1280x768@50Hz, 1280x768@60Hz, 1280x720@60Hz, 1280x800@60Hz, 1280x1024@50Hz, 1280x1024@60Hz, 1280x1024@75Hz, 1366x768@50Hz, 1366x768@60Hz, 1400x1050@50Hz, 1400x1050@60Hz, 1600x1200@50Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@60Hz,