LU9915 Blue Core Laser Projector

The BenQ LU9915 is an innovative laser projector which offers unprecedented flexibility and unrivaled value for large venues. Installation is simplified by a variety of features including 8 optional lenses, motorized shift/lens/zoom/focus and the ability to project at any angle. The LU9915 features BenQ's innovative Blue Core laser technology which provides over 20,000 hours of illumination. Additionally, the reliability and 24/7 operating capability delivers an industry leading total cost of ownership.

Blue Core Laser

Introducing the Blue Core laser from BenQ, an innovative and proprietary technology designed to deliver excellent image quality for large venues. Powered by Digital Light Processing (DLP[®]) technology, the Blue Core laser incorporates a dual color wheel and TIR prism to deliver 10,000 ANSI lumens and an exceptional WUXGA resolution.

Unrivaled Reliability

BenQ's Blue Core laser technology delivers exceptional reliability in even the most demanding applications. Laser technology eliminates the need for lamp replacement, one of the most costly and time intensive aspects of projector maintenance. Additionally, the LU9915 is configured for continuous 24/7 operation and with an operating life of 20,000 hours, the total cost of ownership (TCO) is industry leading.

Installation Flexibility

Installing a professional projector can be a demanding task, but the LU9915 is equipped with a variety of features to simplify things and deliver added flexibility. The projector can be mounted at any angle allowing for impactful visual communication including portrait projection and projecting onto ceilings and floors. Eight selectable all glass lenses maximize projection layout options and ensure a solution for every application. Motorized lens zoom, focus and control allow for last minute changes and eliminate the need for manual re-work.

Key Features

- WUXGA (1920 x 1200)
- 10,000 ANSI Lumens
- 100,000:1 Contrast (Dynamic Black)
- 8 Lens Options, 0.38:1 8.26:1
- Integrated Edge Blending
- Geometric Correction
- 3G-SDI
- HDBaseT

Additional Features

- 360° Any Angle Projection Including Portrait
- Vertical and Horizontal Keystone
- Lens Memory
- Mechanical Shutter
- HDMI, DisplayPort, DVI-D
- Full Keypad for Easy Operation
- Vertical and Horizontal Lens Shift
- Compatible with Crestron, AMX and PJlink Control Systems
- Custom Light Mode Dynamic Brightness for Different Applications



BenQ is a registered trademark of BenQ Corp.All rights reserved. Product names, logos, brands and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice. 171204

Beno

*lens sold separately

SPECIFICATION	IS	LU9915	
	Projection System	DLP [®] 0.67" WUXGA	
DISPLAY	DMD type	DC3 DMD Chip	
	Native Resolution	1920x1200 Pixels	
	Brightness	10000 ANSI Lumens	
	Contrast Ratio*	100,000:1	
	Display Color	1.07 Billion Colors	
	Aspect Ratio Light Source	Native 16:10 (9 aspect ratio selectable) Laser Diodes	
	Light Source life* (Normal/		
	Eco)	20000/45000 Hours	
OPTICAL	Throw Ratio	LS1ST4 Ultra Short Throw: 0.377 LS1ST3 Wide Fix: 0.76 LS1ST2 Ultra Wide: 0.75 ~ 0.93 LS1ST1 Wide Zoom: 1.25 ~ 1.79 LS1SD Standard: 1.73 ~ 2.27 LS1LT1 Semi Long: 2.22 ~ 3.67 LS1LT2 Long Zoom1: 3.58 ~ 5.38 LS1LT3 Long Zoom2: 5.31 ~ 8.26	
	Zoom Ratio	LS1ST4 Ultra Short Throw: Fixed LS1ST3 Wide Fix: Fixed LS1ST2 Ultra Wide: 1.25X LS1ST1 Wide Zoom: 1.41X	LS1SD Standard: 1.3X LS1LT1 Semi Long: 1.65X LS1LT2 Long Zoom1: 1.5X LS1LT3 Long Zoom2: 1.55X
	Lens Control	8 Lens Options (Motorized Zoom and Focus)	
	Lens shift	Vertical: 0% ~ 50% Horizontal: -10%~10%, Standard Lens	
	Keystone Correction	Vertical: ± 30 degrees, Horizontal: ± 30 degrees	
	Projection Size	50" ~ 500", Standard Lens	
AUDIO	Built-in Speaker	NA	
	Security	Security Bar, Power Cord Lock	
SPECIAL FEATURES	Feature	Custom Lightsource Mode (light power adjustment). Dicom Simulation Mode. 2D Keystone. Blank to True Black. Edge-blending. Geometric Correction. 3D Sync. 24/7 Hours Operation. Dust Proof Engine. Dual Liquid Cooling System. Auto High Altitude Mode. 360 Degree & Portrait Projection.	
COMPATIBILITY	Resolution Support	VGA(640 x 480) to WUXGA (1920 x	: 1200)
	Horizontal Frequency	15K - 92kHz	
	Vertical Scan Rate	23 - 85Hz	
	HDTV/UHDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
	Video Compatibility	NTSC, PAL, SECAM	
POWER	Power Consumption (Normal)	1290W@100V, 1215W@240V (Typical)	
	Standby Power Comsumption	Normal < 0.5W. Network < 6W.	
	Power Supply	100 ~ 240V AC	
DIMENSION	MENSION Product Dimensions (WxHxD) 500 X 211 X 583 mm		
AND WEIGHT	Product Weight	28 kg	
OPERATION	Noise Level (Normal/Eco)	42/39 dBA	
CONDITION	Operating Temperature	0 ~ 45°C	
OSD	On-Screen Display Languages	English/ French/ German/ Italian/ Japanese/ Korean/ Portuguese/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Traditional Chinese (12 Languages)	
	Standard	Optional	
ACCESSORIES	Power Cord Remote Control VGA cable (1.8m) Wired Remote Cable Lens Hole Cap Installation Guide Regulatory Statement Anti-Theft Screw	LS1ST4 Ultra Short Throw (5J.JCY37.001) LS1ST3 Wide Fix (5J.JAM37.011) LS1ST2 Ultra Wide (5J.JAM37.061) LS1ST1 Wide Zoom (5J.JAM37.021) LS1SD Standard (5J.JAM37.021) LS1LT1 Semi Long (5J.JAM37.051) LS1LT2 Long Zoom1 (5J.JAM37.031) LS1LT3 Long Zoom2 (5J.JAM37.041)	

LU9915

Blue Core Laser Projector





• HDBaseT(R|45 for

Video Display and

Network control)

• 3D Sync out

3D Sync InWired Remote In

I 2V Trigger

• RS232 In (D-sub 9pin, male)

- HDMI
- DisplayPort
- DVI-D In
- Computer In-1 (D-sub 15pin, Female)
- Computer In-2 (5BNC,YBPBR)
- Monitor out (D-sub 15pin,Female)
- 3G-SDI In
- 3G-SDI Out



* The contrast is measured by Full On/Full Off standard.

* LightSource life results will vary depending on environmental conditions and usage.

 \ast Actual product's features and specifications are subject to change without notice.



BenQ America Corp. www.BenQ.us