# Projecto*Write*8 WX31NXT

| | |
|---|---|
| Model | P8 WX31NXT |
| Technology | .65" WXGA DMD DLP |
| Brightness | 3100 lumens (standard) / 2200 lumens (economy) |
| Native Resolution | 1280 x 800 (WXGA) |
| Supported Resolution | up to 1600 x 1200 (UXGA) |
| Brightness Uniformity | 80%< |
| Projection Methods | Desktop front/rear, Ceiling front/rear |
| Optical Offset | 125% |
| Colors | 1.07 billion true color |
| Color System | NTSC / NTSC 4.43 / PAL (including PAL-M, N) / SECAM/PAL60 |
| Color Wheel | 6 Segment |
| Aspect Ratio | Native 16:10; Compatible 4:3, 16:9 |
| Image Size | 70 in to 100 in /  1.78 m to 2.54 m |
| Projection Distance | 23.5 in ~ 28.7 in 87.2 in diag @ 25.75" |
| Throw Ratio | .35:1    *allow 3-5% variance on all projector throw ratios |
| Speaker | 1 x 10W |
| Contrast Ratio | 3000:1 |
| Digital Zoom | 2x zoom |
| Keystone Correction | Vertical +/– 15 degrees |
| Vertical Scan Rate | 48 to 120 Hz |
| Horizontal Scan Rate | 31 to 92 kHz |
| Lens Type | Fixed zoom / Manual focus |
| Lamp | 280W UHP |
| Lamp Life | 3000 (standard) / 4000 (economy) |
| Remote Control | Multi-function credit card style with battery |
| Noise Level | 37db (standard) / 33db (economy) |
| Power Supply | Universal AC 100 - 240 V ~ 50 - 60 Hz |
| Power Consumption | 345W±10% at 110VAC <.5W in standby mode |
| Safety Certifications | CE, FCC, UL |
| Computer Compatibility | VGA, SVGA, XGA, SXGA, WXGA, UXGA VESA standards; PC and Macintosh compatible |
| Video Compatibility | 480i/p, 576i/p, 720p, 1080i |
| Video Compatibility (HDMI) | SDTV 480P, HDTV 720P, 1080i, 1080p |
| Inputs | VGA x 2, HDMI, S-Video, Composite, Audio RCA (L/R), 3.5mm audio x 2, Microphone, MINI-USB for interactive function |
| Outputs | VGA, 3.5mm audio DC 12V |
| Service and Network Control | RJ45, RS232 D-Sub 9pin |
| Weight | 17.7 lbs / 8 KG |
| Dimensions (W x H x D) | 14.06 in x 14.45 in x 5.32 in / 357 mm x 367 mm x 135 mm |
| Operating Conditions | 41 ~ 104°F |
| Security | Kensington® lock port, anchor security bar |
| Standard Accessories | AC power cord, VGA cable, remote control with battery, user manual (CD), (2) LightPens, USB cable, WallMount-EST |
| Optional Accessories | Replacement remote, cables, Lamps for Life |

*BOXLIGHT's ProjectoWrite8 projector, an ultra short throw interactive projector for when space is tight.*

## KEY FEATURES

● Ships with interactive LightPen dual user annotation software

● Touch mode for enhanced Windows 8 functionality

● Emulate touch screen from projected image

● 3D capable

● Multiple wall color options

● Microphone input

● Filter free design

● Multiple display modes

● Less than 0.5W power consumption in standby mode

● LAN control

LAMPS FOR LIFE

Dual Screen **Link**

**Throw Distance (Feet)**

2.473

2.15

1 73    87    100

70

**Diagonal Image Size (Inches)**

## Award Winning Technical Support 24/7/365

BOXLIGHT products come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.

## BOXLIGHT®
### Presenting a Better Way

360.464.2119
**www.BOXLIGHT.com**