# Seattle X22N

### Brilliance on a Budget

The Seattle X22N - a perfect classroom companion! All the inputs you want, all the brightness you need, with a price tag that fits into your budget.

Classroom perfection!







## Seattle X22N

### **Specifications**



#### **BRIGHTNESS**

2200 Lumens (Standard) 1650 Lumens (Economy)

#### RESOLUTION

1024x768 XGA (Native) 1600x1200 UXGA (Compatible)

#### **DISPLAY TYPE**

0.63" LCD x 3

#### **CONTRAST RATIO**

500:1

#### **ASPECT RATIO**

4:3 Native 16:9 Compatible

#### **THROW RATIO**

1.45 ~ 1.73 (x screen width)

#### PROJECTION LENS

Manual Zoom & Focus

#### **ZOOM RATIO**

1.2:1

#### DIAGONAL IMAGE SIZE

40" - 300" 101.6cm - 762cm

#### **THROW DISTANCE**

3.33' - 25' 1.01m - 7.62m

#### **KEYSTONE**

+/- 30° Vertical

#### LAMP

200 watt UHP

#### LAMP LIFE

2000 (Standard) 3000 (Economy)

#### **INPUTS**

VGA DVI-I Composite S-Video

Component RCA Audio (R/L) Audio x 2 (3.5mm)

#### **OUTPUTS**

VGA

Audio (3.5mm)

#### PROJECTOR CONTROLS

USB

RS232 (9-pin) RJ45 LAN Connection

#### **COMPATIBILITY**

VGA, XGA, SXGA, UXGA, Mac

#### EDTV / SDTV / HDTV

480i/p, 576i/p, 720p, 1080i

#### **FCC CERTIFICATION**

FCC-B, UL, cUL, TUV, CD, CE, CCC

#### VIDEO COMPATIBILITY

NTSC, NTSC 4.43, PAL M/N 60, SECAM

#### **AUDIO**

1 x 8w Mono Speaker

#### **DECIBEL RATING**

33 dB (Standard) / 30 dB (Economy)

#### H-REFRESH RATE

31-92 kHz

#### **V-REFRESH RATE**

48-120 Hz

#### **POWER SUPPLY**

AC 110 ~ 240 Volts 50-60Hz (Auto ranging)

#### POWER CONSUMPTION

285 Watts (Standard) <5w standby

#### DIMENSIONS (WxDxH)

12.8" x 10.24" x 3.8" 32.5cm x 26cm x 9.7cm

#### WEIGHT

7.3 lbs

#### 3.3 kg WARRANTY

3 year parts & labor / 90 day lamp

## Special features of the Seattle X22N include:

**LAN Connectivity**— For network installation. Manage your projectors through a web-based platform.

#### Quick Start Up and Shut Down-

Set up and present quickly, and only a 10 second cool down cycle when you finish.

#### Side Changing Lamp and Filter-

Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.





