
# Seattle X26N

The Classroom Ruler

BOXLIGHT

The Seattle X26N is 2600 lumens of brightness combined with a robust input panel, this is the ideal projector for rooms and classrooms with generous light. The brightest teachers pet.



- LAN control
- Password security
- Closed caption
- RS232
- Optional harsh enviro filter
- Side changing lamp & filter
- Quick startup and shutdown
- 8 watt speaker





# Seattle X26N

# **Specifications**

# BRIGHTNESS

2600 Lumens (Standard) 1700 Lumens (Economy)

#### RESOLUTION

1024x768 XGA (Native) 1600x1200 UXGA (Compatible)

**DISPLAY TYPE** 

0.63" LCD x 3 JLCD

**CONTRAST RATIO** 500:1

**ASPECT RATIO** 

4:3 Native 16:9 Compatible

THROW RATIO

1.45 ~ 1.73 (x screen width)

#### **PROJECTION LENS**

Manual Zoom & Focus

#### **ZOOM RATIO**

1.2:1

## DIAGONAL IMAGE SIZE

40" - 300" 101.6cm - 762cm

Throw Distance (Ft)

# **THROW DISTANCE**

3.33' - 25' 1.01m - 7.62m

## **KEYSTONE**

+/- 30° Vertical

#### LAMP

200 watt UHP

#### LAMP LIFE

2000 (Standard) 3000 (Economy)

#### INPUTS

VGA DVI-I Composite S-Video Component RCA Audio (R/L) Audio x 2 (3.5mm)

## OUTPUTS

VGA Audio (3.5mm) PROJECTOR CONTROLS

USB RS232 (9-pin) **RJ45 LAN Connection** 

#### COMPATIBILITY

VGA, SVGA, XGA, SXGA, UXGA, Mac

EDTV / SDTV / HDTV 480i/p, 576i/p, 720p, 1080i FCC CERTIFICATION

# FCC-B, UL, cUL, TUV, CD, CE, CCC

VIDEO COMPATIBILITY NTSC, NTSC 4.43, PAL M/N 60, SECAM

**AUDIO** 1 x 8w Mono Speaker

DECIBEL RATING 33 dB (Standard) / 30 dB (Economy)

**H-REFRESH RATE** 

31-92 kHz

**V-REFRESH RATE** 

48-120 Hz

# POWER SUPPLY

AC 100 ~ 240 Volts 50-60Hz (Auto ranging)

## POWER CONSUMPTION

285 Watts (Standard) <2.6w standby

# **DIMENSIONS (WxDxH)**

12.8" x 10.24" x 3.8" 32.5cm x 26cm x 9.7cm

WEIGHT

7.3 lbs 3.3kg

# WARRANTY

3 year parts & labor / 90 day lamp


# Special features of the Seattle X26N include:

LAN Connectivity – For network installation. Manage your projectors through a web-based platform.

Quick Start Up and Shut Down— Set up and present quickly, and only a 10 second cool down cycle when you finish.

Side Changing Lamp and Filter-

Easy lamp installation and projector maintenance. No need to remove the projector from ceiling mount position.



**Diagonal Image Size (Inches)** 



www.boxlight.com 360.464.2119

