

# TravelLight3

## Specifications\*



### BRIGHTNESS

2500 Lumens (Standard)

1800 Lumens (Economy)

### RESOLUTION

1024 x768 XGA (Native)

1600X1200 UXGA (Supported)

### DISPLAY TYPE

Texas Instruments

0.55" DMD DLP

### CONTRAST RATIO

1800 :1

### ASPECT RATIO

4:3 Native

16:9 Compatible

### THROW RATIO

1.9 ~ 2.2 (x screen width)

### PROJECTION LENS

Manual Zoom / Focus

### ZOOM RATIO

1.15:1

### DIAGONAL IMAGE SIZE

34" - 260"

### THROW DISTANCE

4.9' - 32.8' Feet

### KEystone

+/- 15° Vertical

### LAMP

200 watt SHP114

### LAMP LIFE

2000 (Standard)

3000 (Economy)

### INPUTS

Audio (3.5mm)

VGA (component)

Composite (3.5 mm)

S-Video (3.5 mm)

### OUTPUTS

N/A

### PROJECTOR CONTROLS

USB

### COMPATIBILITY

VGA,SVGA,XGA,SXGA,

UXGA, Mac

### EDTV / SDTV / HDTV

480i/p,576i/p,720p,1080i

### FCC CERTIFICATION

FCC-B, UL, c-UL

### VIDEO COMPATIBILITY

NTSC / NTSC 4.43 / PAL B/G/H/I/M/N 60 /

SECAM

### AUDIO

1 x 1w Mono Speaker

### DECIBEL RATING

37dB (Standard) / 34dB (Economy)

### H-REFRESH RATE

15, 30-90 kHz

### V-REFRESH RATE

43-87 Hz

### POWER SUPPLY

AC 110 ~ 240 Volts

(auto ranging)

### POWER CONSUMPTION

260W (Standard)

210W (Economy)

<5W standby

### DIMENSIONS (WxDxH)

8.7" x 7.0" x 2.8" Inches

### WEIGHT

3.2 Lbs

### WARRANTY

3 year parts & labor / 90 day lamp

### Special features of the TravelLight3 include:

Upgrade to the industry favorite - TravelLight2 projector!

Extreme portability— Just 3.2 lbs!.

### Fan speed control—

Optional fan speeds for use in high altitude locations.

### Menu reset option—

Reset various settings without defaulting all the projectors settings.

