

# 8922H

## ImagePro 8922H Portable LCD Projector



*The ImagePro 8922H is a light (8.2lbs), easy-to-install / portable LCD projector ideal for classroom or conference room.*

### 8922H FEATURES

- 3200 Lumens Brightness
- XGA Resolution
- Lamp access on top
- High performance (5000 HR) hybrid filter with easy side access
- New 16 Watt Audio Output
- Instant on ON and OFF
- New 3000/6000 hour lamp
- Built-in Anti-theft security
- Audio "passthrough" permits use of sound system to play CDs on the PC when projector is off
- Low 0.5 watt Power Saving Standby Mode



Filter life 5000 HRS

**NEW FRONT-LOADING HYBRID FILTER GIVES  
5000 HOURS OF PROJECTOR PERFORMANCE**

THE ALL NEW  
**DUKANE**  
*Education. Presentation. Inspiration.*

 **Convey**  
SOLUTIONS

Convey by Dukane delivers control of classroom audio visual assets in sync with our Convey AClick Student Response System. Experience tomorrow's classroom today with Convey. Visit [www.conveyclassrooms.com](http://www.conveyclassrooms.com).

Call Dukane: 866.280.4298


Toll-free: 866-280-4298 • Web: [www.dukane.com/av](http://www.dukane.com/av)  
Fax: 630-584-5156 • E-mail: [avsales@dukane.com](mailto:avsales@dukane.com)

# ImagePro 8922H

## Portable LCD projector

### Back Panel

### Connections



### Key features:

- XGA (1024 x 768) resolution
- 3200 ANSI lumens of brightness
- 2001:1 contrast ratio
- Whiteboard & Blackboard Modes
- Easy maintenance in ceiling mount with lamp access on top & 5000 hour filter with front access
- Monitor loophrough & remote mouse control
- Instant On and Off , and 0.5 watt in standby mode
- Built-In Anti-theft security
- Audio passthrough for sound when projector is off
- 16 Watt audio output
- 3000/6000 hour lamp life
- Lock slot, security bar and transition detector
- Five Year Warranty and One Year Peace of Mind Service

### 8922H Projection Table

Image Size 4:3		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	24	2.8	3.4
60	48	5.8	7.0
80	64	7.8	9.3
100	80	9.8	11.7
120	96	11.7	14.1
150	120	14.7	17.6
200	160	19.5	23.5
300	240	29.3	35.3

Throw Ratio (distance to width)      1.46      1.75

# DUKANE

Dukane Corporation  
 Audio Visual Products Division  
 2900 Dukane Drive  
 St. Charles, Illinois 60174  
 866-280.4298  
 630-584-5156  
 avsales@dukane.com  
 www.dukane.com/av

toll-free  
 fax  
 e-mail



ImagePro is a registered trademark of Dukane Corporation

### Specifications

Image Element	8922H
Brightness	0.63" polysilicon active-matrix TFT x3 3200 ANSI lumens (2700 lumens in Eco Mode)
Resolution	1024 x 768 pixels (H X V), XGA
Contrast	2,000:1 with active iris
Scanning Frequency	fh 15 -106 kHz, fv 50-120 Hz
Lens	Manual zoom (F2.3 - 2.5), 1.2X
Lens Throw Ratio	1.46 - 1.75:1 throw distance to image width
Keystone Correction	Digital, vertical +/-30 deg
Aspect Ratio	4:3, 16:9 selectable
Computer Compatibility	SVGA, VGA, XGA, SXGA, UXGA MAC13" and MAC16"
Video Compatibility	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, Component Video, HDTV (1080i/p, 720p, 576i, 480i/p)
Image Control	Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	210W UHB
Lamp Life	3000 hours (typical) 6000 hours (whisper mode)
Audio Output	2 x speakers, 16 watt
Throw Distance	34" to 423"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, RCA x 3 (1) S-video, Mini DIN 4-pin (1) Composite video, RCA x 1
Inputs, Computer	(2) RGB, 15 pin D-sub
Inputs, Audio	(2) Stereo mini jack: for PC/Access. (1) RCA x 2 (for video)
Outputs, Audio	(1) RCA x 2 adjustable
Outputs, Monitor	RGB, 15 pin D-sub
Outputs, Control	RS-232, 9 pin D-sub USB (Mouse control) USB-B port
Security	Kensington lock slot & Security Bar
Fan Level	35dB, ultra quiet; 29dB Whisper Mode
Closed Caption	CCI, CC2, CC3, CC4, T1,T2,T3,T4
Operating Temperature	41-95 deg F
Power	AC 100-120V, AC 220-240V 50/60 Hz, 330 watt,
Power Saving Mode	0.5 watt in standby mode
Size (WxHxD)	12.5" x 3.9" x 11.3"
Weight	8.2 lbs.
Shipping Weight	14 lbs.
Carton Size	15" x 8" x 19"
Accessories Included	Remote control, batteries, power cord, RGB cable, operators manual, CD.
Safety	UL/C-UL, FCC Class B
Optional Accessories	Lamp 456-8755J Ceiling Mount, Universal; RPM-U Filter; MU06481

Five (5) year limited warranty on parts and labor in North America, lamp is a 90 day warranty (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

Specifications subject to change without notice.

# 5YR