



powered by **webOS TV**

Full Shade Series

Illuminate Outdoor Living, Choose QLED Outdoor TV

QLED 4K Outdoor TV is your bright and brilliant choice for outdoor entertainment. This TV utilizes advanced quantum dot technology, delivering stunningly vivid and accurate colors, along with remarkable brightness and contrast. Whether you're watching your favorite movies or enjoying important sports events, QLED 4K Outdoor TV provides an immersive viewing experience that will leave you amazed.



**Water and dust resistant
(IP55)**



**Smart TV
Powered by Web OS Hub**

Mini LED

**Mini LED with
720 zones***

*55inch: 192 zones, 65inch: 480 zones, 75inch: 720 zones

Technical Specifications

At a Glance

Resolution	4K (2160p)
Screen Size	43, 55, 65, 75
Brightness	700 (typical) / 1000 (peak) nits
High Dynamic Range (HDR)	Yes
LED Panel Type	LED
Backlight Type	Full Array Local Dimming
Smart Platform	LG WebOS

Smart

Chipset	RTD2874W
OS	WebOS
eMMC	8GB
DDR	1.5GB
IO	RJ45, USB2 CVBS IN, AV L IN AV R IN OPTICAL, DVB-S2,DVB-T/T2/C,HDMI3,HDMI 2(*EARC), HDMI1(Debug),USB1,Ci, HEADPHONE
Wifi	802.11a/b/g/n/ac
Bluetooth	5.0

LCD

Size	43	55	65	75
Panel Type	VA	VA	VA	VA
Active Display Area (H x V mm)	941 x 529	1209.6 x 680.4	1428 x 803	1650 x 928
Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
Aspect Ratio	16 : 9	16 : 9	16 : 9	16 : 9
Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz
Response Time (typ.)	6.5 ms	6.5 ms	6.5 ms	6.5 ms
NTSC	72%	72%	72%	72%
Viewing Angle	178°/178°	178°/178°	178°/178°	178°/178°
Backlight Configuration	LED	LED	LED	LED
Operation Life (hours)	50,000	50,000	50,000	50,000

Power

AC Input	100~240VAC±10% , 50 / 60 Hz			
Standby Consumption	≤ 0.5W			
Power Consumption	150	260	370	450

Mechanical

TV dimensions (W x H x D mm)	996 x 584 x 78	1264 x 735 x 78	1483 x 858 x 78	1705 x 983 x 78
Packaging dimensions (W x H x D mm)	1090 x 653 x 213	1353 x 802 x 218	1572 x 931x 218	1795 x 1056 x 218
Net Weight (kg)	16	22	29	36
Gross weight (kg)	21	28	37	44

Audio

Built-In Speakers	Yes
Speaker Output	10 watts
Number Of Speakers	2

Environment

Waterproof Rating	IP55
Operataing Temp. Range	0°C to 40°C
Non-operating Temp.	-20°C to 50°C
Operating Humidity	20~80% RH, non-condensing
Operating Altitude	≤ 2000m