

HyperTouch 65

Outdoor 65 inch Dual-Sided High-Brightness Touch Query Kiosk



High Brightness



10-Point Touch



IP Rating



Monitoring System

Technical Specification

Panel (x 2)

Size	65
Active Display Area (H x V mm)	1428 x 803
Resolution	3840 x 2160
Aspect Ratio	16 : 9
Brightness	2500 nits
Backlight Adjustment	Automatic (Ambient Light Sensor)
Viewing Angle	178°/178°
Backlight Configuration	Direct LED
Operation Life Cycle-mtbf(hours)	50,000

Mechanical

Dimensions(W x H x D)	1100 x 2390 x 300 mm
Net Weight	TBD
Enclosure Material	Galvanized Steel
Finishing	Zinc Powder Coating + Fine Grain Powder Coating
Colour	Black(Ral 9005)+Gray(Ral 7038)
Glass	Tempered Glass, Back Painted Pantone Black C
Touch	10-piont touch

Power

AC Input	110 / 220 VAC , 50 / 60 Hz
Power Consumption	1250 w
Lightning Protection Grade	Class C
Leakage Protection	30mA, 0.1S

Media

HDMI in	x 2
---------	-----

Environmental

IP Rating	IP66
Operating Enviroment	Fully Outdoor
Opertaing Temperature	-20°C~50°C
Operating Humidity	5%~98%
Operating Altitude	≤ 2000m

Optional Features

Keewin Surveillance Application is a Remote Diagnostics System for the remote monitoring of digital displays. The system monitors parameters such as:

• Ambient Temperature • Ambient Humidity • Display Front-Face Activity • Impact Alarm • Flood Alarm • Smoke Alarm • Heater Status
• 12V Power Supply Status • Fan Input Voltage • Fan Status • Door Open / Close • Fan Control • Auto-Control AD Board Power Supply



+86-21-54049988



export@keewin.com



www.keewindisplay.com