

TAILOR MADE

Built to your specifications




Screen Size




Touchscreen




Materials



Colors



Camera



Logo



Technical Specifications

LCD Display

	Dual Side
Size	55
Active Display Area (H x V mm)	1210 x 680
Resolution	3840 x 2160
Brightness	700 nits
Aspect Ratio	16 : 9
Viewing Angle	178°/178°
Backlight Configuration	Direct LED
Operation Life (hours)	50,000

Mechanical

Enclosure Material	Aluminum + Steel
Finishing	Brushing(Aluminum)+High Gloss Coating(Steel)
Colour	White (Ral 9003)
Glass	Tempered Glass,Back Painted Pantone White C

Power

AC Input	100~240 VAC±10% , 50 to 60 Hz
Power Consumption	400w

Environment

Operating Environment	Indoor
Operating Temperature	0°C~40°C
Operating Humidity	10%~80%
Operating Altitude	≤ 2000m

Media

	(HDMI In) Standard
HDMI Input	HDMI (x 2), 480i, 480p, 720p, 1080i , 1080p , 2160p

Mechanical

W x H x D	850 x 1980 x 165 mm
Net Weight	190 kg

Optional

Touch
Android
Computer
Camera
NFC
RFID
Ultrasonic sensor

Optional Features

Keewin Surveillance Application is a Remote Diagnostics System for the remote monitoring of digital displays. The system monitors parameters such as:

• Ambient Temperature • Ambient Humidity • Display Front-Face Activity • Impact Alarm • Flood Alarm • Smoke Alarm • Heater Status
• 12V Power Supply Status • Fan Input Voltage • Fan Status • Door Open / Close • Fan Control • Auto-Control AD Board Power Supply