

ZH406STx

Compact high brightness short throw laser projector



- **Bright Full HD 1080p laser projector - 4200 lumens for use any time of day**
- **Short throw lens - 100" image from just over a few feet away**
- **Ultimate Control - Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **DuraCore laser technology - Laser light source provides up to 30,000 hours of virtually maintenance-free operation**



The ZH406STx is a compact short throw Full HD 1080p DuraCore laser projector. Designed for virtually maintenance-free, continuous operation it can be installed in almost any orientation.

Packed full of features this compact laser projector has built-in speakers, is 4K and HDR compatible, and is low maintenance with extremely long-life laser technology. For ultimate control, the projector comes with RJ45 connection allowing you to monitor and control your network in multiple rooms.

Perfect for business, education and museums where a clear, bright image is required.

Specifications

Display/image	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	4,200 lumens
Contrast ratio	300,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - horizontal	+/-15°
Keystone correction - vertical	+/-15°
Has vertical auto keystone correction	Yes
Displayable colors (millions)	1073.4
Horizontal scan rate	15.375 ~ 91.146 KHz
Vertical scan rate	50 ~ 120Hz/Hz
Uniformity	80%
Screen size	36.4" ~ 300.5" diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.5:1
Projection distance	15.75" - 129.92"
Zoom type	Fixed
Focal length (mm)	7.51mm/0.296"
Native offset	115%
Connectivity	
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x Mic 3.5mm Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x micro USB service, 1 x 3D sync
General	
Noise level (typical)	30dB
Noise level (max)	32dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
2D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D compatibility	Full 3D
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Remote control	Backlit ProAV remote
Heat dissipation	918BTU/hour
Speaker count	2
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
Optional wireless models	UHDCast Pro, QuickCast Bundle, QuickCast starter kit
Networking	
LAN - control	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	<0.5W
Power consumption (min)	206W
Power consumption (max)	269W
Weight and dimensions	
Dimensions (W x D x H)	13.27" x 10.43" x 4.82"
Gross weight	13.71 lbs
Net weight	10.03 lbs

