

ZK810T

High brightness professional 4K UHD laser projector





- 8500 lumen 4K UHD DuraCore laser projector -High brightness for immersive installations
- Full motorized lens shift Easy to set up
- Dust resistant Independently tested, IP5X certified
- Long life Delivers 30,000 hours of virtually maintenance free operation



Spectacular 4K UHD image quality, low maintenance and ultimate reliability

The ZK810T 4K UHD laser projector is perfect for fixed installations within education, museums, houses of worship, large venues, simulation or immersive applications.

Specifications

UPC: 796435 44 720 5, EAN: 50 Display/image	
Display technology	DLPTM
Resolution	UHD (3840x2160)
Brightness	8,500 lumens
ANSI brightness	7.200
Contrast ratio	
	3,000,000:1
Contrast ratio - full on/off	1,100:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-40°
Displayable colors (millions)	1073.4
Horizontal scan rate	15.375~91.146Khz
Vertical scan rate	24~85Hz
Uniformity	95%
Screen size	50" ~ 300" diagonal
Lamp info	
Light source type	DuraCore Laser
LASER life	30,000 hours
Optical	
Throw ratio	1.26:1 ~ 2:1
Projection distance	52.36" - 514.17"
Zoom	1.6
Zoom type	Motorised
Focal length (mm)	18.72~29.59
Lens shift	Vertical: +/-55%, Horizontal: +/-25%
Lens shift	Yes - {{downloads_link}}
Connectivity	
	Wired remote Outputs 1 x HDMI 2.0, 1 x USB-A power 1.5A, 1 x Audio 3.5mm, 1 x 3D sync Control 1 x HDBaseT 4K, 1 x RJ45, 1 x 12V trigger, 1 x POPO2
LAN - wireless networking	RS232 No
General	110
Noise level (min)	34dB
Noise level (max)	38dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP5X
OSD / display languages	11 languages: Dutch, English, French, German, Indonesian, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish
24/7 operation	Yes
	Yes
360° operation	
	Backlit ProAV remote
Remote control	Backlit ProAV remote 2
Remote control Speaker count	
Remote control Speaker count Watts per speaker	2
Remote control Speaker count Watts per speaker	2 10W
Remote control Speaker count Watts per speaker	2 10W QSG Back lit remote control Power cable
Remote control Speaker count Watts per speaker	2 10W QSG Back lit remote control
Remote control Speaker count Watts per speaker In the box	2 10W QSG Back lit remote control Power cable
Remote control Speaker count Watts per speaker In the box Networking	2 10W QSG Back lit remote control Power cable
Remote control Speaker count Watts per speaker In the box Networking LAN - control	2 10W QSG Back lit remote control Power cable AAA Batteries
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking	2 10W QSG Back lit remote control Power cable AAA Batteries Yes
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power Power supply	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power Power supply Power consumption (standby)	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power Power Power consumption (standby) Power consumption (min)	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W 280W
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power Consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W 280W 530W
Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN Power Power consumption (standby) Power consumption (min) Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H)	2 10W QSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W 280W 530W 19.13" x 17.03" x 7.3"
360° operation Remote control Speaker count Watts per speaker In the box Networking LAN - control LAN - wireless networking LAN - Verther the second	2 10W OSG Back lit remote control Power cable AAA Batteries Yes No Yes AC 100 – 220 V @ 50/60 Hz 0.5W 280W 530W





Copyright © 2024 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change at any time. 16042024031940