

ZU500USTe

High brightness WUXGA ultra short throw laser projector









- Bright WUXGA laser projector 5,000 lumens
- Ultra short throw lens 100" image from less than
 2-feet away
- DuraCore laser technology 30,000 hours maintenance-free laser light source
- Dust resistant Independently tested, IP5X certification for total reliability



The ZU500USTe is powered by long-lasting, low maintenance DuraCore laser light source. The lamp-less and filter-free design vastly reduces running costs for a low total cost of ownership.

Weighing only 12.35 lbs, this projector can be mounted just inches from a wall or surface and can project an image size of over 100 inches.

Supporting 24/7 operation and versatile orientation, the ZU500USTe is a flexible, powerful and bright ultra short throw projector which makes for a superb signage solution where space or accessibility can be limited, such as shop windows or retail displays.

Specifications

Gross weight Net weight

UPC

Opecifications	
Display/image	
Display technology	DLP™
Resolution	WUXGA (1920x1200)
Brightness	5,000 lumens
Contrast ratio	100,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	16:9,16:10
Uniformity	85%
Screen size	93" ~ 120" diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance	10.6" - 12.6"
Zoom type	Fixed
Focal length (mm)	3.7mm/0.146"
Native offset	120%
Connectivity	
Connections	Inputs 2 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1
	x Composite video, 1 x Audio 3.5mm, 1 x Mic 3.5mm
	Outputs 1 x VGA shared with VGA2, 1 x Audio 3.5mm, 1 x USB-A power 0.5A
	Control 1 x USB-A reader, 1 x RS232, 1 x RJ45
General	33dB
Noise level (typical)	
Noise level (max) PC compatibility	35dB
2D compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
2D compatibility	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
	720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP5x
OSD / display languages	18 languages: Arabic, Danish, Dutch, English, Finnish, French, German, Italian, Japanese, Norwegian, Polish, Portuguese,
	Russian, Chinese (simplified), Spanish, Chinese (traditional),
	Turkish
24/7 operation	Yes
Operating conditions	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
	humidity 85%
Remote control	Backlit ProAV remote
Heat dissipation	1,608BTU/hour
Speaker count	1
Watts per speaker	10W
In the box	AC power cord
	Remote control 2x AAA batteries
	Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit,
<u> </u>	WHD200, WUSB
Networking	
LAN - control	Yes
LAN	Yes
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	250W
Power consumption (max)	400W
Weight and dimensions	
Dimensions (W x D x H)	15.08" x 12.52" x 4.37"
Gross weight	18.72 lbs
Not weight	15 92 lbe

15.92 lbs **796435 44 558 4**

