

ET-WM300



Wireless module

SPECIFICATIONS

Power Supply	Supplied from the projector.
Standard	IEEE 802.11b/g/n
Modulation	Direct sequence spread spectrum (DSSS) system, Orthogonal frequency division multiplex (OFDM) system
Transmission Speed (Standard)*1	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to 150 Mbps
Frequency Range (Channel)	2,412 - 2,472 MHz (1 - 13 ch)
Access Method	Infrastructure mode, ad-hoc mode*2
Security	WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WEP (128 bit/64 bit) When mounted on the PT-FW430/FX400: PEAP (MS-CHAPv2), PEAP (GTC), EAP-TTLS (MD5), EAP-TTLS (MS-CHAPv2), EAP-FAST (MS-CHAPv2), EAP-FAST (GTC), EAP-TLS
Antenna	Tx 1, Rx 1
Interface	USB 2.0 (Cannot be used with any projector other than a Panasonic projector with ET-WM200 compatibility.)
Dimensions (W x H x D) (mm)	23 x 9 x 63 mm
Dimensions (W x H x D) (inch)	29/32 inch x 11/32 inch x 2-15/32 inch
Weight	Approx. 10 g*3 (0.4 ozs*3)
Operating environment*4 Temperature	0° - 45°C (32° - 113°F)
Operating environment*4 Humidity	20% - 80% (no condensation)
Note	*1 This is a theoretical speed. The actual transfer speed varies depending on the usage environment and connected devices. *2 Not supported by IEEE 802.11n. *3 Average value. May differ depending on models. *4 Conforms to the environmental conditions of the mounted projector.

URL: <https://business.panasonic.co.uk/visual-system/et-wm300>

CONTACT

Web: <https://business.panasonic.co.uk/visual-system/contact-us>