Easy Wireless Stick

This product is to be plugged into the USB port of a computer, and contains a built-in wireless LAN adaptor and application software. It enables an easy wireless connection to applicable Panasonic projectors.

Specifications

Standard: IFFF 802.11b/g/n

Modulation: Direct sequence spread spectrum (DSSS) system. Transmission speed (standard)*1: Orthogonal frequency division multiplex (OFDM) system

IEEE 802.11b: Up to 11 Mbps, IEEE 802.11g: Up to 54 Mbps,

IEEE 802.11n: Up to 150 Mbps

2,412-2,472 MHz (1-13 ch) Frequency range (channel):

Access method: Ad-hoc mode*2 Security: WEP (128 bit/64 bit)

System requirements:

Windows® XP: Professional 32-bit SP2/SP3, Home Edition 32-bit SP2/SP3 OS Microsoft®

> Ultimate 32-bit/64-bit, Business 32-bit/64-bit, Home Premium Windows Vista®:

> > 32-bit/64-bit, Home Basic 32-bit/64-bit, compatible up to SP2

Ultimate 32-bit/64-bit, Professional 32-bit/64-bit, Home Premium

32-bit/64-bit, compatible with up to SP1

Windows® 8*3: Windows® 8 Pro 32-bit/64-bit, Windows® 8 32-bit/64-bit

Apple Mac OS X: v10.6, v10.7, v10.8*3

CPU Microsoft® A CPU with at least the minimum specifications to run the above OS. However, in the

case of Windows® XP, Intel Pentium® III 1.2 GHz or faster, or compatible processor.

Apple A CPU with at least the minimum specifications to run the above OS.

Memory with at least the minimum specifications to run the above OS. However, in the Memory

case of Windows® XP, at least 256 MB.

Interface: USB 2.0

Dimensions (W \times H \times D): $36 \times 10 \times 93$ mm (1-13/32 × 13/32 × 3-21/32 inches)

Windows® 7:

Weight: Approx. 20 q*4 (0.7 ozs*4)

Operating environment: Temperature: 5-35 °C (41-95 °F), humidity: 20%-80% (no condensation)

Applicable projector: PT-VW435N/VX505N/VX400NT

PT-VW345NZ/VX415NZ*3

PT-FW300NT/F300NT/F200NT/FW100NT/F100NT

PT-LB90NT/LW80NT/LB80NT/LB75NT/LB60NT/LB55NT/LB51NT/LB50NT


Applicable projector when the

ET-WM200 is attached: PT-DZ570/DW530/DX500/FW430/FX400

- *1 This is a theoretical speed. The actual transfer speed varies depending on the usage environment and connected devices.
- Not supported by IEEE 802.11n.
- *3 In order to use with Windows® 8/Apple Mac OS X v10.8 or to connect to the PT -VW345NZ/VX415NZ. it will be necessary to update the firmware to the latest version.
- *4 Average value. May differ depending on products.

Dimensions

SFL12A013-1



unit : mm (inch) NOTE: This illustration is not drawn to scale.

36 (1-13/32)



Weights and dimensions shown are approximate. Specifications subject to change without notice.