

## Wireless presentation system for standard meeting rooms



ClickShare makes connecting to the meeting room's video system a matter of clicking a button. This one click wonder not only helps the presenter get the presentation on-screen in a second, but it also allows the other people in the meeting to participate more actively. This is done using the unique ClickShare Button, or by installing a simple app to share content from an Android or iOS smartphone or tablet. The result is enhanced meeting efficiency and better decision-making.

### **Instantly on screen, using any device**

A ClickShare CSM-1 set consists of two USB-powered devices (the 'ClickShare Buttons') and a Base Unit. The Base Unit has a fixed connection to the meeting room's visualization system, and takes care of all the needed processing. Users who want to get their presentation on the large meeting room screen, simply connect a Button to their PC or MAC. They start the application, click the ClickShare Button and immediately their desktop is wirelessly transferred to the large visualization system. Alternatively, when using a smartphone or tablet (either iOS or Android-powered), a simple app allows you to share content as well.

### **A new meeting dynamic**

ClickShare changes the way you meet. Instead of focusing on one presenter, ClickShare encourages all attendees to participate. By showing visual content on the large meeting room screen, it becomes easier for everybody to prove their point. The system's stability and ease-of-use, also drastically limits the number of needed interventions by the IT department.

## Product specifications

## CSM-1

<b>General specifications</b>	
<b>Operating system</b>	Windows XP/Vista/7/8/8.1 32 & 64 bit Mac OSX 10.6/10.7/10.8/10.9 Android 2.2 and later (ClickShare Presenter app) iOS 5.0 and later (ClickShare Presenter app)
<b>Video outputs</b>	HDMI (video and audio), 15-pin VGA
<b>Frame rate</b>	Up to 30 fps depending on environment
<b>Output resolution</b>	HDMI: 1280x720 (720P), 1920x1080 (1080p) VGA: SVGA (800x600) / XGA (1024x768) / WXGA(1280x768) / WXGA+(1280x800) / 1360 * 768 / 1440 * 900 / 1600 * 1200
<b>Input Resolutions</b>	Up to 2880x1800
<b>Number of sources simultaneous on screen</b>	1
<b>Number of simultaneous connections</b>	8
<b>Audio</b>	Radio quality 16bits 22KHz (no synchronization) via audio jack or HDMI
<b>iPad, iPhone and Android compatibility</b>	Available via ClickShare Presenter app for static content.
<b>Authentication protocol</b>	WPA2-PSK
<b>Wireless transmission protocol</b>	IEEE 802.11 a/b/g/n
<b>Data rate wireless</b>	Up to 300Mbps
<b>Reach</b>	Max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit
<b>Band</b>	2.4 GHz and 5 GHz
<b>Power</b>	External Power adaptor 5V DC input 2.6A (included in set)
<b>Connections</b>	USB Host x 2 RJ-45 LAN Port Audio analog line out on mini jack socket (3.5mm)
<b>Temperature range</b>	Operating: 0°C to +40°C (+32°F to +104°F) Storage: -10°C to +60°C (+14°F to +140°F)
<b>Humidity</b>	Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 80% relative humidity, non-condensing
<b>Wall mounts</b>	Included in set
<b>Certifications</b>	FCC/CE
<b>Warranty</b>	3 years standard
<b>ClickShare Base Unit dimensions</b>	
<b>Dimensions (HxWxD)</b>	Excl. antennas: 37mm x 186mm x 85mm / 1.457" x 7.323" x 3.346" Incl. antennas: 125mm x 186mm x 121mm x / 4.921" x 7.323" x 4.763"
<b>Weight</b>	530g / 1.17lbs (incl. antennas)