



# XJ-A247 SLIM SERIES

The thinnest, high brightness projector -  
1.7 inches thin – the length and width  
of a sheet of paper and weighs only 5 lbs.

CASIO® Laser & LED Hybrid Light Source

LampFree® Projector



## XJ-A247



### LampFree Features:

- 2500 lumens
- 2X power zoom
- Input/output connectivity—RGB, video, HDMI, RS-232C, audio in/out
- Built-in 1W speaker
- DLP technology
- Auto brightness adjustment
- On screen presentation timer
- Closed captioning
- WXGA (1280 x 800) resolution

### USB:

- Wireless presentations from PC or Mac
- Built-in memory: 2GB
- Logo Capture – start up screen
- Presentations from your thumb drive
- USB display: send video to the projector from almost any device via an inexpensive USB cable

### LampFree Benefits:

- Laser & LED Hybrid Light Source
- Mercury Free
- Quick Start (8 seconds to full brightness)
- Instant Off – no cool down required
- 20,000 Hour Operating Life
- No Lamp Replacement
- No Down Time
- Low Power Consumption
- Intelligent Brightness Control

### Continuous Operation:

The cool-running XJ-A247 Slim Line projector has the ability to run all day, every day in extended-use applications\* including digital signage, museum displays and other challenging environments. Run the XJ-A247 worry-free, knowing you will not shorten its expected life or damage the projector's bright, high-impact images. (Projectors must be reset once a day when operated in continuous operation applications).


\* Extended Use Applications are defined as operation of 10 hours per day for 5 or more days per week. Under these conditions the light source warranty is one (1) year or 6000 hours.

### Low Carbon Footprint:

Eco Mode can save as much as 50%, and we link it to an ambient light sensor, producing great images by automatically adjusting the projector brightness to the brightness of the room.

### Warranty Information:

3 year warranty on the projector and 3 years (or 6,000-hour usage) on the light source.



## CASIO Projector Specifications

		Slim Series XJ-A247
		WXGA
Native Resolution		1280 x 800
Native Aspect Ratio		16:10
Brightness		2500 lumens
Display Device		0.65-inch DLP® chip
Contrast Ratio		1800:1
Lens Type		2X Power Zoom & Focus
Lens Specs F/f		F2.29-3.09/f15.9-30.8mm
Lens Offset		33%
Light Source		Casio Laser & LED Hybrid (Up to 20,000 Hours)
Screen Size (Min-Max)		18 to 300-inch diagonal
Projection Range	60-inch screen	4.6 ~ 9.3 ft
	100-inch screen	7.9 ~ 15.8 ft
	Minimum Throw Distance	2.8 ft
	Throw Ratio	1.15-2.30:1
Keystone Correction		Vertical +30° (Auto) Vertical + or - 30° (Manual)
Color Reproduction		Full color (16.77 million colors)
Power Source		AC100~240V, 50/60Hz
Power Consumption		Bright mode : 155W Eco 1 mode : 115W
	Standby	0.14 w (no LAN Models)
<b>TERMINAL CONNECTIVITY</b>		
<b>Video Signal Compatibility</b>		
	Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
	DTV/HDTV	480i/480P/576i/576P/720P/1080i/1080p
	Maximum Computer Input	UXGA (1600 x 1200)
<b>INPUTS</b>		
RGB/Component Video Input		mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input— commercially available adapter required)
HDMI		HDMI Type A x 1 (480p~1080p)
USB Display		Yes
Composite Video		Stereo Mini x 1
Audio		(Shared with Stereo Audio in/out)01200
Built-in Memory		Yes
		2GB (PDF, JPEG, BMP, PNG, GIF, AVI,MOV,MP4)
USB		Type A (USB2.0) x1 / Micro B(USB2.0) x1
Logo Transfer		Micro B(USB1.1) x1
Wireless Capability	IEEE802.11 b/g/n compatible	Wireless LAN Adapter (YW-40) is included with USB Models
<b>OUTPUTS</b>		
Audio		Stereo Mini x 1 (Shared with Stereo Audio in/out)
Microphone (dynamic compatible)		No
<b>AUDIO AND CONTROL SYSTEMS</b>		
Audio system		1W x1 Monaural Speaker
Control Terminal		
	RS-232	RS-232C (Mini Din) x 1 Optional YK-60 cable require and sold separately. Straight cable required
Control System Compatibility		AMX, Crestron, Extron, SP Controls, PJLink
<b>OTHER INFORMATION</b>		
<b>Usage Environment</b>		
	Operating Temp/Humidity	41~95°F / 20~80% (non condensation)
	High Altitude Mode	Yes (for operation 5,000~10,000 ft)
Extended operation (24 x 7)		Yes – Note: Projector must be turned off once every 24 hours
Rotation Projection		90 degrees Left/Right (Portrait) Only
Remote Control Range		16.4 ft Maximum
Security Compatibility		Kensington™ Compatible / Power On Password
Ceiling Mountable		Yes, available and sold separately by 3rd party vendors
Ceiling Mount Screws		(Type x Qty) M3 x 3, not included (Insert depth 4-6 mm)
Limited Warranty		3 years Parts and Labor plus 3 years or 6,000 hours light source, see Warranty Statement included with product for complete details.
Included Accessories		Wireless remote control, YW-40 Wireless adapter, 6' RGB cable, AV Cable, 6' AC Power Cord, Carry Bag, Setup Manual (Printed)
Included Software		Network Connection (Windows® and Mac) EZ-Converter FA (Windows®)
Optional Accessories		YK-60 (RS-232C adapter)
Cabinet Color		White / Light Grey Trim
Dimension (W x D x H)	Including Projections	11.69 x 8.26 x 1.69 in
	Excluding Projections	11.69 x 8.26 x 1.59 in
Weight		5.1 lbs
<b>Packing Information</b>		
	Carton Dimensions	14.96" W x 6.22" H x 10.43" D
	Carton Weight	10.14 lbs
UPC Code		079767466824
Manufactured in		Japan