

The dnp Supernova Flex Classic is a traditional version of the award-winning dnp Supernova Flex Screen.

It offers the superior optical performance of a Supernova Flex Screen in a classic, retractable design.



dnp optical front projection screens

If you are looking for a flexible AV solution for meeting rooms and home entertainment, dnp Supernova Flex Classic is the answer. It combines revolutionary Supernova Screen technology with a proven design concept. Unlike the high-end dnp Supernova Flex Screen, which is suspended by wires, the Classic version is mounted with dark grey drop above the image area, allowing the retractable screen to be rolled down to the desired height.

dnp Supernova Flex Classic is fitted with high-contrast filters that absorb ambient light and deliver exceptionally clear images even in brightly lit surroundings – eliminating the need to darken the room. The screen is therefore ideal for bright meeting rooms and home entertainment applications in living rooms, which are often designed to maximize natural light.

The screen is operated from a remote control, and the noiseless electrical motor ensures that it slides up into its sleek housing quickly and easily.

The screen comes with a white housing, which can be mounted onto the wall or ceiling. It is easy to install, compatible with all standard projectors and comes with a IR remote control for easy operation.

- > Retractable optical dnp Supernova Screen in classic design
- > For on-wall or ceiling mounting
- > Front projection for environments with high ambient light
- > Best-in-class black-levels and perfect colour balance
- > High brightness uniformity
- > Noiseless retraction
- > Easy IR remote control operation + potential free contact closure (via RJ45 socket)
- > ISF-certified screen material

Application suitability						
Auditorium/sports arena	*	*				
Conference room	*	*	*	*	*	*
Control room	*					
TV studio	*	*				
Advertising – in-store	*	*	*	*		
Advertising – window display	*					
Home entertainment – bright living room	*	*	*	*	*	*
Home entertainment – darkened home theatre	*	*	*	*		







dnp Supernova™ Flex Classic

Specifications

Product details					
Aspect ratio		16:10 format	0 - "	"	16:9 format
Screen size		100"	84"	100"	120"
Part no.	230V	5 100 7 000 26	5 084 6 000 26	5 100 6 000 26	5 118 6 000 26
Part no.	110 V	5 100 7 000 21	5 084 6 000 21	5 100 6 000 21	5 118 6 000 21
Image area					
Width	mm	2154	1860	2214	2612
Height	mm	1346	1046	1245	1469
Area	m2	2.90	1.95	2.76	3.84
Width	inches	84.8	73.2	87.2	102.8
Height	inches	53.0	41.2	49.0	57-9
Area	ft2	31.2	20.9	29.7	41.3
Housing dimensions					
Width	mm	2444	2150	2504	2902
Height	mm	95	95	95	95
Depth	mm	95	95	95	95
Width	inches	96.2	84.6	98.6	114.3
Height	inches	3.7	3.7	3.7	3.7
Depth	inches	3.7	3.7	3.7	3.7
Shipping dimensions					
Length	mm	2755	2460	2815	3215
Height	mm	200	200	200	200
Width	mm	210	210	210	210
Length	inches	108.5	96.9	110.8	126.6
Height	inches	7.9	7.9	7.9	7.9
Width	inches	8.3	8.3	8.3	8.3
Weight					
Screen (net)	kg	14	13	14	16
Shipping (gross)	kg	21	18	21	23
Screen (net)	lbs	31	28	31	35
Shipping (gross)	lbs	46	40	46	51
Projection information					
Minimum lens throw ratio	ltr	1.5:1	1.5:1	1.5:1	1.5:1
Minimum projection distance	mm	3231	2789	3321	3918
	ft	10.6	9.2	10.9	12.9

Subject to change without notice. Please check specifications at time of ordering.







dnp Supernova™ Flex Classic

General information

General information					
Available screen material		08-85			
Peak gain Horizontal half-gain angle Lens pitch	。 micron	o.8 85 65			
Drop		ver. 2.02	Other ver.		
Maximum drop length (standard)	mm	400*	боо*		* Fully adjustable from zero to max
Maximum drop length (standard)	inches	15,7*	23.6*		
Masking frame					
Width	mm	50			
Width	inches	2.0			
Screen controls					
Standard	IR remote control	+ potential free cont	act closure (via RJ45 so	ocket)	
Motor options	Voltage (V~)	Freq. (Hz)	Power (W)	Current (A)	Speed (rpm)
Option 1	220-240	50	98	0.85	28
Option 2	100-120	60	102	0.43	33
Operating environment					
Temperature Temperature	°C °F	10-40 50-104			
Humidity (non-condensing)	%RH	10-70			
Housing					
Colour Material	White Aluminium				
Mounting		to screen	to bottom bar		
Distance from wall	mm inches	20 0.8	10		
	inches	0.0	0.4		

Included in the package

Screen, IR remote control, power cord without plug, wall mounts, product guide

Certificates







dnp optical screens have won numerous awards including the Best Buzz Award at InfoComm, Honoree Awards at CES and the ExcIte award at CEDIA US 2007.













