

Home Cinema 5020UBe Wireless 3D 1080p 3LCD Projector















Brilliant Wireless 1080p 2D & 3D Entertainment.

 One measurement of brightness is not enough — look for both high color brightness and high white brightness. The Home Cinema 5020UBe has:

Color Brightness – 2400 lumens¹ White Brightness – 2400 lumens¹

- Rich, vibrant color and reliable performance 3LCD, 3-chip technology
- Amazing, true-to-life color built-in cinema filter with an expanded color gamut
- Wireless HDMI connect all your favorite devices wirelessly; includes 5 HDMI inputs, 1 HDMI output and 1 optical port
- A true cinematic experience 2D and 3D, Full HD 1080p technology
- Accurate picture quality THX display certification
- Widest horizontal lens shift in its class horizontal and vertical lens shift for flexible, easy setup
- Exquisite detail a contrast ratio of up to 320,000:1 for the most discerning AV enthusiasts
- Great picture uniformity and positioning flexibility state-of-the-art Fujinon[®] lens with a 2.1x zoom ratio
- 2D-to-3D conversion easily transform 2D images into spectacular 3D for unlimited 3D content
- Split Screen³ (now available in wireless mode) project two images side-by-side from two different sources
- Outstanding support two-year limited warranty; two-business-day replacement with free shipping⁴





Home Cinema 5020UBe Wireless 3D 1080p 3LCD Projector

| Product Code | UPC |
|--------------|--|
| V11H529020 | 0 10343 90409 5 |
| V11H529020-F | 0 10343 90417 0 |
| V13H010L69 | 0 10343 88651 3 |
| V13H134A39 | 0 10343 88653 7 |
| V12H548006 | 0 10343 90476 7 |
| | V11H529020 V11H529020-F V13H010L69 V13H134A39 |

Specifications

Projection System

EPSON 3LCD, 3-chip technology

Projection Method

Front / Rear / Ceiling mount

Product Color White and Black

Driving Method

EPSON Poly-silicon TFT Active Matrix, 0.74-inch wide panel with MLA

Projected Output HD, 2D, 3D, 1080p

Pixel Number

2,073,600 dots (1920 x 1080) x 3

Color Brightness

Color Light Output: 2400 lumens White Brightness¹

White Light Output: 2400 lumens

Aspect Ratio

Native 16:9 widescreen (4:3 resize) Compatible with 4:3 and 2.35:1 video formats with Normal, Full or Zoom Modes

Native Resolution

Native 1080p (1920 x 1080)

Resize

16:10, 4:3

Lamp Type E-TORL® 230 W UHE

Lamp Life²

Up to 5000 hours (Eco mode) Up to 4000 hours (Normal mode)

Throw Ratio Range

1.34 - 2.87

Size (projected distance)

30" - 300" (Zoom: Wide and Zoom: Tele)

Keystone Correction

Vertical: ± 30 degrees (Manual)

Contrast Ratio Up to 320,000:1

Color Reproduction

Full-color (1.07 billion colors)

Color Processing

Full 10 bit (Partial 12 bit)

Projection Lens

Type

Manual Focus / Optical Zoom

F-number

2.00 - 3.17

Focal Length

Zoom Ratio

Vertical: -96.3% to +96.3% Horizontal: -47.1% to +47.1%

Lens Cover

Powered, Slide Lens Shutter

Other

Display Performance

1920 x 1080 native 1080p; HD, 2D, 3D, 2D to 3D conversion

Color Modes

2D: Dynamic, Living room, Natural, THX, Cinema 3D: 3D Dynamic, 3D Cinema, 3D THX

EPSON Cinema Filter

Automatically adjusts to color mode; (On: Natural/THX/Cinema; Off: Dynamic/Living Room/3D Dynamic/3D Cinema/3D THX)

Auto Iris in 2D & 3D

Automatically adjusts to video source; User selectable (High speed/Normal/Off)

Input Signal

Composite: NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM Component: 480i / 576i / 480p / 576p / 720p /

1080i / 1080p HDMI: TMDS

Terminal Inputs

2 x HDMi, RS-232c, 1 RCA (composite), 3 RCA (component), 2 RCA (audio L/R) stereo, 1 VGA D-sub 15 pin (computer input)

Terminal Outputs

Trigger On/Off (3.5 mm stereo jack) 12 VDC 200 mA (max.)

Computer Compatibility

Operating Temperature 41 °F to 95 °F (5 °C to 35 °C)

Power Supply Voltage 100 – 240 VAC ± 10%, 50/60 Hz

Power Consumption

Lamp on 364 W, Lamp on (Eco) 274 W, Standby (HDMI Link on/off) .27 W

Fan Noise

22 - 32 dB

Security

Kensington Security Lock Port

Dimensions (W x D x H)

Including feet 18.4" x 15.6" x 6.2" Excluding feet 18.4" x 15.6" x 5.5" Weight 18.9 lb

Remote Control

HDMI 1 & 2

Features

Front and rear directional

Operating Distance 32 ft (10 m)

Operating Angle

± 30 degrees

WirelessHD Transmitter

Video

Component

Power Consumption

11V 1 2A

Operating Altitude

0 to 7500 ft

Storage Temperature 14 °F to 140 °F (-10 °C to 60 °C)

Dimensions

6.9" x 5.0" x 2.0" (W x D x H)

Safety UL 60950-1 2nd edition (cTUVus Mark)

EMC FCC Part 15B Class B

Wireless FCC Part 15 Subpart C 15.255

Input HDMI x 5

Output HDMI x 1, Optical Audio x 1, USB Type A x 1 (3D Glasses Charging)

WirelessHD type

Beam Forming WirelessHD 1.0b 60 GHz Band (QPSK, 16-QAM, BPSK) 2 ch and 3 ch

Parental Controls

Power Button Lock

Hinders projector from being turned on without parental supervision

Support

The EPSON ConnectionSM

Pre-sales support U.S. and Canada 800-463-7766 Internet website www.epson.com

Service Programs

Two-year projector/One-year 3D glasses limited warranty, EPSON Home Service program, PrivateLine® dedicated toll-free support (U.S. and Canada only) and 90-day limited lamp warranty

What's in the Box

PowerLite Home Cinema 5020UBe projector, power cord, two HDMI cable clamps, remote control with AA batteries, CD-ROM with user guide link, 2 pairs of RF 3D glasses, wireless transmitter with AC adapter, 3D glasses charging cable, Quick Setup Guide

Optional Accessories

Kensington® Security-

Lock Port

Computer

RS-232c

Trigger Out

Power

Genuine EPSON lamp V13H010L69 Replacement air filter V13H134A39 RF 3D glasses V12H548006 Projector ceiling mount CHF1000 1582262 Remote control Belkin Pro Series VGA / SVGA cable - 6 ft F3H982-06 Belkin Pro Series VGA / SVGA F3H982-10 cable - 10 ft Belkin Pro Series VGA / SVGA F3H982-25 cable - 25 ft Belkin PureAV HDMI audio video AV22300-03 cable – 3 ft Belkin PureAV HDMI audio video cable - 6 ft AV22300-06 Belkin PureAV HDMI audio video AV22300-12 cable - 12 ft Kensington Security Lock ELPSL01 Repair/Exchange 1-year EPPSNVHTRB1 extended service plan Repair/Exchange 2-year

Packaging Specifications

FPPSNVHTRR2

PowerLite Home Cinema 5020UBe 20.1" x 23.0" x 13.5" (W x D x H) Weight 26.91 lb

Genuine EPSON Lamp

extended service plan

6.3" x 5.6" x 5.6" (W x D x H) Weight 0.80 lb

Air Filter

6.0" x 3.3" x 1.7" (W x D x H) Weight 0 10 lb

Ceiling Mount

13.0" x 13.4" x 4.3" (W x D x H) Weight 6.40 lb

3D Glasses 2.3" x 3.3" x 7.0" (W x D x H) Weight 0.33 lb

Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4;

white light output measured in accordance with ISO 21118.

Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time.

Subject to product availability. Extra Care™ Home Service orders must be in by 3 p.m. Eastern Time for Two-Business-Day delivery. SmartWay Transport Partne

Better Products for a Better Future

Epson America, Inc.

3840 Kilroy Airport Way, Long Beach, CA 90806

Consult your user manual for input combinations.

eco.epson.com

Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON, E-TORL and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine is a registered trademark and EPSON Connection is a service mark of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2012 Epson America, Inc. 8/12

CPD-37672 Product Setup Sheet 2