

C550X

5000:1 / 5500 Lumens



C560W

5000:1 / 5000 Lumens



C5 Series

Super Bright, Highly Capable, Feature-Rich



5000:1 Contrast Ratio

With a 5000:1 contrast ratio, you're ensured of rich picture layering details and clear, crisp images for even the most demanding viewers.



High Brightness for Large Images

Super bright at 5000 and 5500 Lumens, the C5 Series is a great projector solution for meeting rooms, conference rooms and other small to large type environments.



Vertical and Horizontal Keystone Correction/Corner Keystone (March Hybrid-Filter & Powerful Cooling System

Horizontal and vertical digital keystone correction fixes image distortion created when a projector's lens is not perpendicular to the screen. Corner keystone correction allows the adjustment of all four angles of the image. These are ideal tools for when the projection environment is less than ideal.



Each projector is furnished with a low-maintenance, replaceable dust filter that effectively reduces smoke and dust from entering the projector. The cooling system is optimized for powerful heat dispersion, even at high altitudes.



Simple, Quick Operational Set Up

Automatic or Manuel Keystone correction makes sure that the projected image is ideal, despite projector placement. Automatic image reversal can be done without a menu setting when installed from ceiling.



1.65x Standard Digital Zoom Lens

Compared to standard 1.2x lenses, the C5 projectors feature a 1.65x zoom lens that meets various installation requirements.



Vertical and Horizontal Lens Shift

Allows easy installation and mounting of the C5 Series projectors in nearly any room or enviornment



Network Control

With a wired connection via RJ45, control or monitor all projectors through corresponding IP. Turn the projectors on/off, check configurations, view lamp times and operational status through the network.

Portable Projectors





Specifications

Model	C550X	C560W	
Display Technology	Liquid Crystal Display		
Display Panel	3 x 0.63"	3 x 0.59"	
Brightness	5,500 ANSI Lumens	5,000 ANSI Lumens	
Native Resolution	XGA (1024x768)	WXGA (1280x800)	
Contrast Ratio	5000:1	5000:1	
Throw Ratio	Min Zoom: 2.47 - Max Zoom: 1.48		
Projector Lens	1.65x, F+1.6 - 2.08, f = 19.36 - 31.94mm		
Uniformity	80%		
Distance / Screen Size (Diagonal)	35" - 598"	37" - 628"	
Aspect Ratio	4:3 (Standard), 16:9 (Compatable)	16:10 (Standard), 4:3 (Compatible)	
Keystone	V: ± 30° (Auto) H: ± 15° (Manual) Corner Keystone		
Input	HDMI, 2-VGA, YCbCr, S-Video, Video, 2-USB Audio: 3.5 Mini-Jack, RJ45	HDMI, 2-VGA, YCbCr, S-Video, Video, 2-USB Audio: 3.5 Mini-Jack, RJ45	
Output(s)	VGA, Audio Out, 12V Trigger		
Control	RS-232, RJ-45		
PC Compatibility	VGA, SVGA, XGA, WXGA, UXGA, Mac		
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, and 1080i		
Lens Shift H.	±10% (Manual)		
Lens Shift V.	±40% (Manual)		
_amp	280 Watts		
Lamp Life	(STD Mode) 4000 Hours, (ECO Mode) 6000 Hours		
Lamp Replacement	Top Lamp Replacement		
Remote Control	Yes		
H. Synch Freq.	15 - 100KHz		
V. Synch Freq.	48 - 85Hz		
Standby Power	< 0.3 Watts		
Power Supply	100V - 240V @ 50 - 60Hz		
Operating Temp.	32°F - 104°F		
Storage Temp.	68°F - 140°F		
OSD Languages	23 languages inclduing English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Protuguese, Japanese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Czech, Vietnamese, Thai, Farsi		
Speaker	10 Watts		
Dimensions	15.2" x 12.1" x 4.3"		
Weight	10.7 lbs		
Standard Accessories	User Manual (CD), Power Cord, Rem	User Manual (CD), Power Cord, Remote Control, VGA Cable, Warranty Card	



Other Features:

- 1. 360° Lens Shift
- 2. One Touch Blank Screen
- 3. Quick Power off
- 4. Custom Startup Logo
- 5. Auto Image Reverse 11. Top cover lamp replacement
- 6. Built in Test Images 12. Anti-Theft Bar & Lock
- 7. Closed Caption
- 8. Image Zoom in/out