



High Performance, High resolution Widescreen Installation WUXGA (1920 x 1200) Projector with HDBaseT™, 3D Surround Sound Audio and 3D Video Ready

Features

- High 5500 lumens of brightness with a 10,000:1 contrast ratio
- Native WUXGA (1920 x 1200) DLP® dark chip 3 and BrilliantColor™ technologies for sharp and detailed image quality
- Centered lens for easy installation
- Horizontal and Vertical lens shift
- Horizontal and Vertical Keystone correction
- HDBaseT™ interface with support for distribution of HD video and digital audio content over CAT5e/6LAN cable
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Full 3D capability for Blu-Ray and Broadcast
- 3D sync port for compatibility with IR (infrared) 3D passive
- 14W of total 3D audio surround sound power (7W x 2) with multiple audio-in and audio-out ports
- 12V trigger for simple screen/projector automation port for direct communications and automated control of such devices as screens and curtains
- RJ45/RS-232c for integration and system automation compatible with Crestron, AMX, Extron, and Telnet
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments
- Dual remote infrared sensors (Front and Rear)
- Anti-theft security features: Kensington® security slot, and security bar



| Specifications | | | | |
|-------------------------------|---|----------------|--------------------------------|-----------|
| Brightness (Typical) | 5500 ANSI Lumens | | | |
| Native Resolution | WUXGA (1920 x 1200) | | | |
| Max. Resolution | WUXGA (1920 x 1200) @60Hz | | | |
| Contrast Ratio | 10,000:1 (Full On/Off) | | | |
| Lamp Life and Type | 1,500/3,500 Hours (Normal/Eco), 370W/280W | | | |
| Lamp Part # | 5811119760-SVV | | | |
| Display Type | Single 0.67" DLP® Technology by Texas Instruments | | | |
| Throw Ratio (±3%) | 1.25 to 2.13:1 (Distance/Width) | | | |
| Image Size (Diagonal) | 21.8" to 371.4" | | | |
| Projection Distance | 3.28' to 32.8' (1.0 to 10 m) | | | |
| Projection Lens | F=2.45 – 3.22, f=18.8 – 32mm | | | |
| Zoom Ratio | 1.7:1 Manual Zoom/Focus | | | |
| Aspect Ratio | 16:9 Native, 4:3 Compatible | | | |
| Offset | 122.4% / 111.2% | | | |
| Keystone Correction | ± 30° Vertical, Horizontal ± 25° | | | |
| Color Spectrum | 1.07 Billion | | | |
| Horizontal Scan Rate | 15, 31 ~ 91.4KHz | | | |
| Vertical Scan Rate | 24 ~ 30Hz, 47 ~ 120Hz | | | |
| 3D Functionality | Full 3D (Via DLP® Link™, Blu-ray and Broadcast 3D) | | | |
| Speaker | 3D Audio Surround Sound (7Wx2) | | | |
| Lens Shift Range | Vertical: +29%, -13% Horizontal: +/-10% | | | |
| Remote Control | Fully Featured IR Remote | | | |
| Projection Method | Table Top or Ceiling Mount (Front or Rear) | | | |
| Uniformity | 85% | | | |
| Computer Compatibility | WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible | | | |
| Video Compatibility | HDTV (1080i/p, 720p), SDTV(480i, 576i), EDTV (480p, 576p), SDTV(480i, 576i), NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM | | | |
| I/O Connection Ports | HDMI v1.4 (x2) | HDMI 1/MHL | Microphone-In (Mini-Jack) | |
| | | HDMI 2 | 12-Volt Trigger (Mini-Jack) | |
| | VGA-In (x2) | | 3D Sync | |
| | VGA-Out | | RJ45 | |
| | DVI-D | | RS-232 | |
| | Component/RGBHV (5 BNC) | | Power-Out (5V/2.0A) USB Type A | |
| | S-Video | | Wire Remote In/Out (Mini-Jack) | |
| | Composite | | Service Only (USB Type B) | |
| | Audio-In | RCA L/R | Audio-Out | RCA L/R |
| | | Mini-Jack (X3) | | Mini-Jack |
| HDBaseT™ | | | | |
| Security | Kensington® Lock Port, Security Bar | | | |
| Weight | 18.5lbs (8.4kg) | | | |
| Dimensions (W x D x H) | 17.5" x 12.9" x 6.3" (445 x 330.2 x 162mm) | | | |
| Noise Level | 30dB/36dB (Eco/Normal) | | | |
| Power | Supply: AC 100-240V, 50/60Hz Consumption: 380W/480W (Eco/Normal) <0.5W (Standby Mode), <6W (LAN Standby) | | | |
| Operating Temperature | 41 to 104°F (5 to 40°C) | | | |
| Warranty | 3-Year Limited Parts/Labor, 1-Year Lamp | | | |
| Standard Accessories | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, User Manual (CD), Warranty Card | | | |
| Optional Accessories | Wireless Collaboration System NovoConnect B360 | | | |
| | Wireless Collaboration System NovoPro Replacement Lamp | | | |
| UPC | 813097020369 | | | |

