



DU6771-WH

Large Venue Presentation

Large Venue Presentation
Solution for Demanding
Multimedia Applications



Features

- 6,500 ANSI lumens with a dynamic 3,000:1 contrast ratio for an amazing image quality
- 16:10 aspect ratio with native resolution support up to WUXGA (1920 x1200)
- Dual-lamp engine design to create a brighter bigger image and 24/7 operational reliability
- Airtight sealed optical engine and high-density filter to reduce the impact of dust and improve performance
- Innovative six segment color wheel for outstanding color reproduction
- Powered zoom, focus and lens shift (horizontal/vertical) for easy adjustment and positioning flexibility
- Centered lens with horizontal (-14% to 24%) and vertical (-33% to 64%) lens shift range for hassle-free installation
- Lens Positioning Memory (LPM) enabled for up to 10 user assigned settings for lens position, lens shift, focus, and zoom
- Eight (8) high performance interchangeable lens options with quick touch lens release design for easy removal and reinstallation
- 3D compatibility with DLP® Link™ and HDMI v1.4 technology support (Bluray, side by side, frame packing, top and bottom) for dazzling and realistic life-like images
- Full suite of display I/O ports including: HDMI v1.4a (x2), DVI-D, Component (5 BNC), VGA-In, Monitor-Out, HDBaseT™
- HDBaseT® interface with support for transmission of HD video, Ethernet control, RS-232 control and infrared control signal over one standard CAT5e/6 LAN cable
- 360° installation for flexible placement in a wide variety of environmental conditions (Portrait mode not supported)
- Crestron® RoomView™ certified for network monitoring and management
- Anti-theft security features include: Kensington® security slot, security bar, PIN lock keypad and anti-theft lens screw



DU6771-WH

SPECIFICATION

Display Type	Single Chip 0.67" DLP Technology by TI
Brightness	6,500 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200)
Maximum Resolution	WUXGA (1920 x 1200) @60Hz,Reduced Blanking
Contrast Ratio	3,000:1
Lamp Life/Type	3,000/4,000 Hours (Normal/Eco. Mode), UHP 300W/240W x 2
Throw Ratio*	1.73 - 2.27:1
Image Size (Diagonal)*	40" - 500"
Projection Distance*	1.83 - 14.9m (6.0ft - 48.88ft)
Projection Lens*	F = 1.7 - 1.9 f = 26- 34mm
Zoom Ratio*	1.3x
Aspect Ratio	16:10
Keystone Correction	Horizontal $\pm 30^\circ$, Vertical $\pm 30^\circ$
Horizontal Frequency	15, 31 - 91.4kHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
3D Compatibility	DLP® Link™, HDMI v1.4 (Blu-ray, side by side, frame packing, top and bottom)
Lens Shift Range*	Vertical: -33%/+64%, Horizontal: -14 - 24% (Motorized)
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA@60hz, Mac
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p)
I/O Connection Ports	HDMI v1.4 (x2), DVI-D, VGA-In, Component (5 BNC) (RGBHV), 3D-Sync In, 3D-Sync Out, Monitor Out, 12V Trigger, RS-232, USB (Service), Remote Jack (Wired Remote), RJ45/ HDBaseT™ (Shared Port)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Pin Lock, Keypad, Anti-Theft Lens Screw
Dimensions (WxDxH)	510 x 470 x 210mm (20.1"x 18.5" x 8.3")
Weight (W/O Lens)	20kg (44.1lbs)
Available Colors	White (DU6771-WH), Black (DU6771-BK)
Noise Level	35dB/30dB (Normal/Economy Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	Dual Lamp: 715W (Normal Mode), 575W (Eco.Mode), <3W (Network Standby), <0.5W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Body Cap, , R/C Wire 3.5mm Jack, Documentation Kit
Optional Accessories	Replacement Lamp, Interchangeable Lens Options (x8), Interchangeable Color Wheel Module
	*Note: Standard Lens

TEL: +1-855-885-2378 | WWW.VIVITEKUSA.COM | 46101 FREMONT BLVD., FREMONT, CA 94538 USA

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.