



**Versatile, Brilliant, and High Performance  
widescreen WXGA Installation Projector with  
HDBaseT connectivity, 3D Surround Sound Audio  
and 3D Video Ready**

**Features**

- High 6000 lumens of brightness with a 10,000:1 contrast ratio
- Native WXGA (1280 x 800) DLP® dark chip 3 and BrilliantColor™ technologies for sharp and detailed image quality
- Centered lens for easy installation
- Horizontal and Vertical lens shift
- Horizontal and Vertical Keystone correction
- HDBaseT interface with support for distribution of HD video and digital audio content over standard CAT5e/6 LAN cable
- MHL device compatibility for streaming of video and audio content from a compatible mobile device
- Full 3D capability for Blu-Ray and Broadcast
- 3D sync port for compatibility with IR (infrared) 3D passive
- 14W of total 3D audio surround sound power (7W x 2) with multiple audio-in and audio-out ports
- Multi Media and Wireless features
- 12V trigger for simple screen/projector automation port for direct communications and automated control of such devices as screens and curtains
- RJ45/RS-232c for integration and system automation compatible with Crestron, AMX, Extron, and Telnet
- Top-loading, sliding cover for quick and easy lamp replacement
- Keypad lock prevents accidental system adjustments



Specifications	
<b>Brightness (Typical)</b>	6000 ANSI Lumens
<b>Native Resolution</b>	WXGA (1280 x 800)
<b>Max. Resolution</b>	WUXGA (1920 x 1200) @60Hz
<b>Contrast Ratio</b>	10,000:1 (Full On/Off)
<b>Lamp Life and Type</b>	1,500/3,500 Hours (Normal/Eco), 370W/280W
<b>Lamp Part #</b>	5811119760-SVV
<b>Display Type</b>	Single 0.65" DLP® Technology by Texas Instruments
<b>Throw Ratio (±3%)</b>	1.32 to 2.24:1 (Distance/Width)
<b>Image Size (Diagonal)</b>	21" to 360" (0.053 to 8.93m)
<b>Projection Distance</b>	3.28' to 32.8' (1.0 to 10 m)
<b>Projection Lens</b>	F=2.45 – 3.22, f=18.8 – 32mm
<b>Zoom Ratio</b>	1.7:1 Manual Zoom/Focus
<b>Aspect Ratio</b>	16:10 Native, 4:3, and 16:9 Compatible
<b>Offset</b>	134.3% / 117.1%
<b>Keystone Correction</b>	± 30° Vertical, Horizontal ± 25°
<b>Color Spectrum</b>	1.07 Billion
<b>Horizontal Scan Rate</b>	15, 31 ~ 91.4KHz
<b>Vertical Scan Rate</b>	24 ~ 30Hz, 47 ~ 120Hz
<b>3D Functionality</b>	Full 3D (Via DLP® Link™, Blu-ray and Broadcast 3D)
<b>Speaker</b>	3D Audio Surround Sound (7Wx2)
<b>Lens Shift Range</b>	Vertical: +24%, -13% Horizontal: +/-11%
<b>Remote Control</b>	Fully Featured IR Remote
<b>Projection Method</b>	Table Top or Ceiling Mount (Front or Rear)
<b>Uniformity</b>	85%
<b>Computer Compatibility</b>	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
<b>Video Compatibility</b>	HDTV (1080i/p, 720p), SDTV(480i, 576i), EDTV (480p, 576p), SDTV(480i, 576i), NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
<b>I/O Connection Ports</b>	HDMI v1.4, MHL/HDMI v1.4, VGA-In (x2), DVI-D, Component (5 BNC) (RGBHV), S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack)(x3), Microphone-In (Mini-Jack), Wired Remote-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), Audio-Out RCA (L/R), 12v Screen Trigger (Mini-Jack), 3D Sync-Out, RS-232, USB Type A (File Reader/USB Host), USB Type B (Service), USB Display (MINI B), USB Type A (Wireless Dongle), , Wired Remote-Out (Mini-Jack), RJ45, HDBaseT
<b>Security</b>	Kensington® Lock Port, Security Bar
<b>Weight</b>	15lbs (6.8kg)
<b>Dimensions (W x D x H)</b>	17.5" x 12.9" x 6.3" (445 x 330.2 x 160.2mm)
<b>Noise Level</b>	33dB/39dB (Eco/Normal)
<b>Power</b>	Supply: AC 100-240V, 50/60Hz Consumption: 430W/530W (Eco/Normal) <0.5W (Standby Mode)
<b>Operating Temperature</b>	41 to 104°F (5 to 40°C)
<b>Warranty</b>	3-Year Limited Parts/Labor, 1-Year Lamp
<b>Standard Accessories</b>	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, User Manual (CD), Warranty Card
<b>Optional Accessories</b>	Wireless Collaboration System NovoConnect B360
<b>UPC</b>	813097020321

